



d5411

TIZU PENDANT


PROJECT:
TYPE:
QUANTITY:
NOTES:

SPECIFICATION

CONSTRUCTION	Spun-aluminum or solid-copper shade
ACCENTS	Wood finial
MOUNTING	Standard ceiling junction box
CORD	White, three-conductor hanging cord
FINISH	Metal or powder coat paint
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or medium base socket
DIMMING	Non-dimming, 0-10V, ELV, or TRIAC
SHADE DIMENSION	9-1/2" diameter x 18-1/4" height
OVERALL HEIGHT	60"
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



DIMENSIONS



RELATED PRODUCT: d5185



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
☐ d5411	LED⁶ 6W LED, 540 TOTAL LUMENS LED⁸ 8W LED, 736 TOTAL LUMENS 1M100⁸ 100W MAX, MEDIUM BASE, A TYPE	120¹ 120V 277 277V	PAINTED FINISHES BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK MG METALLIC GREY YL BRIGHT YELLOW WH WHITE GLOSS SPECIAL COLOR FINISH SCF _____	INCP³ INNER SHADE IN RAW COPPER DIM⁴ DIMMING: 0-10V, ELV, OR TRIAC STEM⁵ RIGID 1/2" DIAMETER STEM TR⁷ FOR USE WITH TRACK SYSTEMS EMP⁶ EMERGENCY BATTERY PACK METAL FINISHES AL BRUSHED ALUMINUM PA POLISHED ALUMINUM COPPER FINISHES CPL POLISHED COPPER (LACQUERED) CBL BRUSHED COPPER (LACQUERED) CPU POLISHED COPPER (UNLACQUERED) CBU BRUSHED COPPER (UNLACQUERED)
NOTES 1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE 3. STANDARD FIXTURE WITH INNER SHADE PAINTED WHITE 4. SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC 5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH 6. REQUIRES A SEPARATE EM DRIVER THAT MAY AFFECT THE INSTALLATION AND PROFILE OF THE FIXTURE 7. ADAPTER AND TRACK SUPPLIED BY INSTALLER 8. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 9. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE				



Phone: 203.775.1805
P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
dacLighting.com | cs@dacLighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice