



d5420/5421

APERTO PENDANT

PROJECT:
TYPE:
QUANTITY:
NOTES:

SPECIFICATION

CONSTRUCTION	Spun aluminum shade
ACCENTS (D5421 ONLY)	Polished chrome trim, clamps and loop White opal acrylic diffuser
CANOPY	5" diameter black canopy
MOUNTING	Standard ceiling junction box
STEM	Adjustable rigid stem
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED
DIMMING DRIVER	Optional dimming driver: 0-10V, ELV, or TRIAC
SHADE DIMENSION	12.13" diameter x 16" height
OVERALL HEIGHT	60"



DIMENSIONS



CANOPY OPTION



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
☐ d5420	LED12 ² 12W LED WITH ELECTRONIC DRIVER LED16 ² 16W LED WITH ELECTRONIC DRIVER LED35 ⁶ 16W LED WITH ELECTRONIC DRIVER	120 ¹ 120V 277 277V	PAINTED FINISHES BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK MG METALLIC GREY YL BRIGHT YELLOW BC BLACK CRINKLE G1 LIGHT GREY OR ORANGE	TR ³ FOR USE WITH TRACK SYSTEMS DIM ⁴ DIMMING: 0-10V, ELV, OR TRIAC WH WHITE GLOSS T2 MEDIUM TAN AN METALLIC ANTHRACITE SF SEAFOAM MP MAGENTA PINK BZ METALLIC BRONZE SPECIAL COLOR FINISH SCF
☐ d5421 ⁵	NOTES 1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. ADAPTER & TRACK SUPPLIED BY OTHERS 4. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC 5. WITH POLISHED CHROME TRIM, CLAMPS, AND LOOP 6. ONLY AVAILABLE IN A 120V, NON-DIMMING CONFIGURATION 7. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE			



Phone: 203.775.1805
P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
dacLighting.com | cs@dacLighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice