



d5238



d5239

d5238
d5239



Item #	Lamping	Voltage	Shade Finish	Options	Sp. Orders
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

How to specify

d5239	-2F13	-120	-AL		
-------	-------	------	-----	--	--

Work space for submittals

Example from illustration at left

Item Number d5238 BASIX 14 1/4" x 3 1/2" pendant
d5239 BASIX 14 1/4" x 8 1/4" pendant

Construction Aluminum shade and canopy. White opal, acrylic bottom lens. Aircraft cable supports fixture. Height adjustable after installation. Black, 3 conductor cord exits black, 5" diam. canopy. For standard ceiling junction box mounting. UL listed, cUL certified for dry locations.

Lamping/Wattage

for d5238

3C25	Incandescent, three 25 W, candelabra base, B-10 type
1FC40	Fluorescent, one 40 W Circline, T5 type, 2GX13 base, electronic HPF ballast
2FC22/40	Fluorescent, one 22 W and one 40W circline, T5 type, 2GX13 base

for d5239

1N100	Incandescent, one 100 W, medium base, A type
2F13	Fluorescent, two 13 W quad, 4 pin, electronic HPF ballast
2F18	Fluorescent, two 18 W quad, 4 pin, electronic HPF ballast
2F26	Fluorescent, two 26 W triple tube, 4 pin, electronic HPF ballast

All fixtures supplied less lamps. Lamps may be ordered from d'ac.

Voltage 120 120V 277 277V

Shade Finishes

AL Brushed Aluminum	G1 Light Grey	G2 Medium Grey
WH White Gloss	AN Metallic Anthracite	BG Black Gloss
MG Metallic Grey	BC Black Crinkle	C1 Metallic Copper
MB Matte Black	T1 Light Tan	T2 Medium Tan
BZ Metallic Bronze	SF Seafoam	BL Metallic Blue
GM Metallic Green	RB Bright Red	MP Magenta Pink
RD Metallic Red	OR Orange	
YL Bright Yellow	SCF Special Finish – must supply paint chip	

Options **COIL** – Coiled electrical cord. **STEM** – Rigid 1/2" diam. stem.

Special Orders For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative.