



d8100-1FM13-120-RB



d8101-1N75-120-BL



Item #	Lamping	Voltage	Shade Finish	Options	Sp. Orders
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

How to specify

Work space for submittals

Example from illustration at left

d8100	-1FM13	-120	-RB	<input type="text"/>	<input type="text"/>
-------	--------	------	-----	----------------------	----------------------

Item Number	d8100 d8101	BASIX 7 1/4" x 3 7/8" ceiling/wall fixture ADA BASIX 7 1/4" x 8 5/8" ceiling fixture
Construction	Aluminum shade. White opal, acrylic bottom lens. For standard ceiling junction box mounting. UL listed, cUL certified for dry locations.	

Lamping/Wattage		
for d8100	2C25	Incandescent, two 25 W, candelabra base, B-10 type
	1FM13	Fluorescent, one 13 W quad, 2 pin, electromagnetic NPF ballast
for d8101	1N75	Incandescent, one 75 W, medium base, A type
	1F13	Fluorescent, one 13 W quad, 4 pin, electronic NPF ballast
	1F18	Fluorescent, one 13 W quad, 4 pin, electronic HPF ballast
	1F26	Fluorescent, one 26 W triple tube, 4 pin, electronic HPF ballast
<i>All fixtures supplied less lamps. Lamps may be ordered from d'ac.</i>		

Voltage	120	120V	277	277V
---------	-----	------	-----	------

Shade Finishes		
AL Brushed Aluminum	G1 Light Grey	G2 Medium Grey
WH White Gloss	AN Metallic Anthracite	BG Black Gloss
MG Metallic Grey	BC Black Crinkle	C1 Metallic Copper
MB Matte Black	T1 Light Tan	T2 Medium Tan
BZ Metallic Bronze	SF Seafoam	BL Metallic Blue
GM Metallic Green	RB Bright Red	MP Magenta Pink
RD Metallic Red	OR Orange	
YL Bright Yellow	SCF Special Finish – must supply paint chip	

Special Orders	For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative.
-----------------------	---