



Dijkstra Lampen design



d1331-1FT24-120-AL

d1331: 28 1/4"
d1333: 51 3/4"



rotatable shade



Item #	Lamping	Voltage	Finish	Options	Sp. Orders
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Work space for submittals

How to specify

Example from illustration at left

d1331	-1FT24	-120	-AL	<input type="text"/>	<input type="text"/>
-------	--------	------	-----	----------------------	----------------------

Item Number

d1331
d1333

EPOS 28 1/4" wall sconce
EPOS 51 3/4" wall sconce
Dijkstra Lampen

Construction

Aluminum body. Pop-out acrylic diffuser.
210 degree adjustable shade for direct or indirect lighting.
Electronic ballast integrated in the fixture.
No outlet box required. The fixture is designed to have BX cable mounted directly to the back of the fixture. The base of the fixture acts as the wiring chamber and the BX conduit fitting mounts directly to the back of the fixture mounting bracket. If an outlet box is to be used, the specifier, contractor and/or distributor must notify d'ac. Upon notification, d'ac will supply a secondary mounting plate to cover a horizontally mounted 2" x 4" outlet box. Fixture still requires wall anchors.
UL listed, cUL certified for dry and damp locations.

Lamping / Wattage

For d1331 -1FT24
For d1333 -1FT54

Fluorescent, one 24 W HO, miniature bi-pin, T5 type, electronic HPF ballast
Fluorescent, one 54 W HO, miniature bi-pin, T5 type, electronic HPF ballast
All fixtures are supplied less lamps. Lamps may be ordered from d'ac.

Voltage

120 120V 277 277V

Finish

AL Brushed Aluminum

Options

BI Dual apertures allowing bi-directional light from the top & bottom (d1331 only)
OB Modification for mounting fixture to an outlet box

Special Orders

For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative.