

RNH-HKF design



d5020-1N150-120-WH-CL



Item #	Lamping	Voltage	Metal Finish	Shade Color	Options	Sp. Orders
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Work space for submittals

How to specify

Example from illustration at left

d5020	-1N150	-120	-WH	-CL	<input type="text"/>	<input type="text"/>
-------	--------	------	-----	-----	----------------------	----------------------

Item Number d5020 12" diam. LEXY pendant
d5021 16" diam. LEXY pendant

Construction Acrylic prismatic shade. 5" diam. steel canopy. Aluminum components. White, three conductor hanging cord. For standard ceiling junction box mounting. UL listed, cUL certified for dry locations.

Lamping / Wattage 1N150 Incandescent, one 150 W, medium base, A type
Fixtures supplied less lamps. Lamps may be ordered from d'ac.
 1F18 Fluorescent, one 18 W quad, 4 pin, electronic HPF ballast
 1F26 Fluorescent, one 26 W triple tube, 4 pin, electronic HPF ballast
 1F32 Fluorescent, one 32 W triple tube, 4 pin, electronic HPF ballast
 1F42 Fluorescent, one 42 W triple tube, 4 pin, electronic HPF ballast
 1M70* Metal Halide, one 70 W, medium base, ED-17 type
 *Remote "F-can" magnetic metal halide ballasts not to exceed 10 feet from lamp; items must use bottom lens (see below)

Voltage 120 120V 277 277V

Finishes See Page d9000 for color renderings

AL Brushed Aluminum	PA Polished Aluminum	<i>Baked Enamels:</i>
WH White Gloss	G1 Light Grey	G2 Medium Grey
MG Metallic Grey	AN Metallic Anthracite	BG Black Gloss
MB Matte Black	BC Black Crinkle	CU Metallic Copper
BZ Metallic Bronze	T1 Light Tan	T2 Medium Tan
GM Metallic Green	SF Seafoam	BL Metallic Blue
RD Metallic Red	RB Bright Red	MP Magenta Pink
YL Bright Yellow	SCF Special Finish—must supply paint chip	

Standard Shade Colors CL Clear GR Green BL Blue
MK Milky white AM Amber RD Red

Options BHC Black, three conductor hanging cord STEM Rigid, 1/2" diam. stem
 BLF Acrylic bottom lens—flat (clear) BLD Acrylic bottom lens—dome (clear)
 CEQ California Earthquake Swivel—must use rigid stem
 ELTRN Remote electronic metal halide ballast, 120 V
 Not to exceed 12 feet from lamp

Special Orders For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative.