



d'ac studio design





| Item # | Lamping | Voltage | Finish | Options | Sp. Orders |
|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |

Work space for submittals

How to specify

Example from illustration at left

| | | | | | |
|-------|--------|------|-----|--|--|
| d5031 | -1N150 | -120 | -BZ | | |
|-------|--------|------|-----|--|--|

| | | |
|---------------------|--|--|
| Item Number | d5031 | 60" ALANZIA pendant / d'ac studio design |
| Construction | Spun aluminum shade. Polished chrome trim and clamps with set screws. White opal acrylic diffuser. 5" diam. black canopy. Adjustable height, aircraft cable supports fixture. 60" overall height. Black, 3 conductor cord. For standard ceiling junction box mounting. UL listed, cUL certified for dry, damp and wet locations. | |

| | | |
|--|--------------|--|
| Lamping / Wattage <i>Fixtures supplied less lamps. Lamps may be ordered from d'ac.</i> | 1N150 | Incandescent, one 150 W, medium base, A type |
| | 1F26 | Fluorescent, one 26 W triple tube, 4 pin, electronic HPF ballast |
| | 1F32 | Fluorescent, one 32 W triple tube, 4 pin, electronic HPF ballast |
| | 1F42 | Fluorescent, one 42 W triple tube, 4 pin, electronic HPF ballast |
| | 1M70* | Metal halide, one 70 W, medium base, ED-17 type |

*Remote ballast on metal halide version not to exceed 15 feet from lamp

| | | | | |
|----------------|-----|------|-----|------|
| Voltage | 120 | 120V | 277 | 277V |
|----------------|-----|------|-----|------|

| | | | |
|---|----------------------------|--|---------------------------|
| Finishes <i>See Page d9000 for color renderings</i> | AL Brushed Aluminum | PA Polished Aluminum | <i>Baked Enamels:</i> |
| | WH White Gloss | G1 Light Grey | G2 Medium Grey |
| | MG Metallic Grey | AN Metallic Anthracite | BG Black Gloss |
| | MB Matte Black | BC Black Crinkle | CU Metallic Copper |
| | BZ Metallic Bronze | T1 Light Tan | T2 Medium Tan |
| | GM Metallic Green | SF Seafoam | BL Metallic Blue |
| | RD Metallic Red | RB Bright Red | MP Magenta Pink |
| | YL Bright Yellow | SCF Special Finish—must supply paint chip | |

| | | |
|----------------|--|--|
| Options | WET - UL listed for wet and damp locations | STEM Rigid, 1/2" diam. stem (aircraft cable and cord replaced by 1/2" diam. rigid stem and modified canopy) |
| | COIL - Coiled electrical cord. Not an option for metal halide | |

| | |
|-----------------------|---|
| Special Orders | For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative. |
|-----------------------|---|