

Heinz K. Filzer design



d5060-1N100-1Z0-PG

d5060-1N100-120-PC



	A	B	C
d5060:	29 1/2"	17 1/2"	3 3/8"
d5061:	35"	25"	4 1/2"
d5062:	40"	33"	5 1/4"

Item #	Lamping	Voltage	Finish	Sp. Orders
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Work space for submittals

How to specify

Example from illustration at left

d5060	-1N100	-120	-PC	
-------	--------	------	-----	--

Item Number

d5060
d5061
d5062

One-lamp pendant, 29 1/2" OAH
Two-lamp pendant, 35" OAH
Three-lamp pendant, 40" OAH

Construction

White opal glass bowl. Steel trim ring with 5 1/8" diam. canopy (for d5060 and d5061) and 6" diam. canopy (for d5062). Aircraft cables support glass and ring. For standard ceiling junction box mounting. UL listed, cUL certified for dry locations.

Lamping / Wattage

Fixtures supplied less lamps.
Lamps may be ordered from d'ac.

Note: d5060 accepts 1 lamp, d5061 accepts 2 lamps and d5062 accepts 3 lamps
...please specify number before lamping code
1, 2 or 3N100 Incandescent, 100 W, medium base, A type
2 or 3F13 Fluorescent, 13 W quad, 4 pin, electronic HPF ballast
2 or 3F18 Fluorescent, 18 W quad, 4 pin, electronic HPF ballast
2 or 3F26 Fluorescent, 26 W triple tube, 4 pin, electronic HPF ballast
2 or 3F32 Fluorescent, 32 W triple tube, 4 pin, electronic HPF ballast
Fluorescent versions incorporate a white opal acrylic disc to shield lamps from viewing.

Voltage

120 120V 277 277V

Finishes

See Page d9000 for color renderings

PC Polished Chrome	Baked Enamels:	
WH White Gloss	G1 Light Grey	G2 Medium Grey
MG Metallic Grey	AN Metallic Anthracite	BG Black Gloss
MB Matte Black	BC Black Crinkle	CU Metallic Copper
BZ Metallic Bronze	T1 Light Tan	T2 Medium Tan
GM Metallic Green	SF Seafoam	BL Metallic Blue
RD Metallic Red	RB Bright Red	MP Magenta Pink
YL Bright Yellow	SCF Special Finish—must supply paint chip	

Special Orders

For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative.