

Hoffmeister-Leuchten design



d5171-1F32-120-MG-BL



d5171-1F32-120-MG-RD

d5171-1F32-120-MG



Item Number	d5170	5 1/2" diam. CORCOVADO pendant
	d5171	7 1/2" diam. CORCOVADO pendant
	d5172	10 3/4" diam. CORCOVADO pendant

Construction Spun aluminum shade. Indirect light exits through center opening. Bottom clear glass lens (d5171 and d5172 only). Internal reflector. Black three conductor cord. Aircraft cables support shade. Height adjustable, 60" overall height. For standard ceiling junction box mounting. UL listed, cUL certified for dry locations.

Lamping / Wattage	For d5170 No bottom lens	1N60 1F13	Incandescent, one 60 W, medium base, A type Fluorescent, one 13 W quad, 4 pin, electronic HPF ballast*
	For d5171 only	1N100 1F26 1F32 1M70† 1M100†	Incandescent, one 100 W, medium base, A type Fluorescent, one 26 W triple tube, 4 pin, electronic HPF ballast* Fluorescent, one 32 W triple tube, 4 pin, electronic HPF ballast* Metal Halide, one 70 W, medium base, ED-17 type Metal Halide, one 100 W, medium base, ED-17 type
For d5172 only	1F42 1M150†	Fluorescent, one 42 W triple tube, 4 pin, electronic HPF ballast* Metal Halide, one 150 W, medium base, ED-17 type	*Ballast enclosed in 5" diam. x 2" deep canopy †Remote "F-can" magnetic ballast not to exceed 10 feet from lamp

Fixtures supplied less lamps. Lamps may be ordered from d'ac.

Voltage	120	120V	277	277V
----------------	------------	------	------------	------

Finish	MG	Metallic Grey
---------------	-----------	---------------

Options	RD	Red color accent filter in center of fixture.
	BL	Blue color accent filter in center of fixture.

Special Orders For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative.

How to specify

Work space for submittals

Item #	Lamping	Voltage	Fixture finish	Options	Sp. Orders

Example from illustration above left

d5172	-1F42	-120	-MG		
-------	-------	------	-----	--	--