



**d8030** STRATO 12 1/2" diam. ceiling fixture/wall sconce ADA  
**d8031** STRATO 18 3/8" diam. ceiling fixture/wall sconce ADA  
**d8032** STRATO 9" diam. ceiling fixture/wall sconce ADA  
**d8033** STRATO 22" diam. ceiling fixture/wall sconce ADA

**d8030, d8031**  
**d8032, d8033**

Dijkstra Lampen designs



d8030-1FF24-120-AL


d8030-1FF24-120-AL  
(As ADA wall sconce)



**d8030 d8032**  
**d8031 d8033**



d8030: 12 1/2"  
d8031: 18 3/8"  
d8032: 9"  
d8033: 22"



← 2 3/4" → d8030  
d8031  
d8033  
← 2 1/2" → d8032

Item #	Lamping	Voltage	Fixture Finish	Sp. Orders
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Work space for submittals

**How to specify**

Example from illustration at left

d8030	-1FC22	-120	-AL	<input type="text"/>
-------	--------	------	-----	----------------------

<b>Item Number</b>	d8030	STRATO 12 1/2" diam. ceiling fixture/wall sconce <b>ADA</b>
	d8031	STRATO 18 3/8" diam. ceiling fixture/wall sconce <b>ADA</b>
	d8032	STRATO 9" diam. ceiling fixture/wall sconce <b>ADA</b>
	d8033	STRATO 22" diam. ceiling fixture/wall sconce <b>ADA</b>
		Dijkstra Lampen design

<b>Construction</b>	Spun aluminum, surface mounted enclosure. Brushed aluminum finish (standard). Opal white glass. Perforated aluminum side diffuser. For standard wall junction box mounting. UL listed, cUL certified for dry locations.	
---------------------	---	--

<b>Lamping / Wattage</b>	1FC22	Fluorescent, one 22 W Circline, T5 type, 2GX13 base, electronic HPF ballast
for d8030	2N60	Incandescent, two 60 W, medium base, T-10 type
for d8031	2FC22/40	Fluorescent, one 22 W and one 40W Circline, T5 type, 2GX13 base, electronic HPF ballast
	3N60	Incandescent, three 60 W, medium base, T-10 type
for d8032	1FM13	Fluorescent, one 13 W quad, 2 pin, electromagnetic NPF ballast
	2C40	Incandescent, two 40 W, candelabra base, B-10 type
for d8033	2FC22/40	Fluorescent, one 22 W and one 40W Circline, T5 type, 2GX13 base, electronic HPF ballast
		<i>All fixtures are supplied less lamps. Lamps may be ordered from d'ac.</i>

<b>Voltage</b>	120	120V	277	277V
----------------	-----	------	-----	------

<b>Fixture Finish</b>	AL	Brushed Aluminum
-----------------------	----	------------------

**Special Orders** For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative.