



# d1270

## CANTO WALL FIXTURE

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_


### SPECIFICATION

<b>CONSTRUCTION</b>	Solid metal sides and backplate
<b>ACCENTS</b>	Metal fascia and knobs
<b>DIFFUSER</b>	Curved opal glass
<b>MOUNTING</b>	Standard wall junction box
<b>FINISH</b>	Metal or powder coat paint
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED
<b>DIMMING</b>	Non-dimming, 0-10V, ELV, or TRIAC
<b>DIMENSIONS</b>	9-3/4" Width x 12-1/4" Height
<b>DEPTH</b>	2-5/8"
<b>CODE COMPLIANCE</b>	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



### DIMENSIONS

### RELATED PRODUCT: d1271



### ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d1270	LED6-L <sup>2</sup> 6W LED, 552 TOTAL LUMENS	120 <sup>1</sup> 120V 277 277V	<b>PAINTED FINISHES</b> BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK MG METALLIC GREY YL BRIGHT YELLOW WH WHITE GLOSS <b>SPECIAL COLOR FINISH</b> SCF _____	<b>DIM<sup>3</sup> DIMMING: 0-10V, TRIAC, OR ELV</b>  <b>METAL FINISHES</b> AL BRUSHED ALUMINUM PA POLISHED ALUMINUM BB BRUSHED BRASS PB POLISHED BRASS
<b>NOTES</b> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED. 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V, ELV, OR TRIAC 4. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE				



Phone: 203.775.0172  
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

*As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice*