



d1280

HANDKERCHIEF WALL FIXTURE


PROJECT: _____
 TYPE: _____
 QUANTITY: _____
 NOTES: _____

SPECIFICATION

SHADE	Acrylic shades with gloss outside and white opal inside
ACCENTS	Polished chrome clips
MOUNTING	Standard wall junction box Fixtures can be mounted in either "Square" or "Diamond" positions
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED
DIMMING	Non-dimming, 0-10V, ELV, or TRIAC
DIMENSIONS	19-3/4" Width x 19-3/4" Height
DEPTH	4"
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



DIMENSIONS



RELATED PRODUCT: d1600



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	SHADE OPTIONS	CLIP FINISHES
d1280	LED12 ² 12W LED, 1102 TOTAL LUMENS	120 ¹ 120V 277 277V	RD RED GR GREEN BL BLUE YL YELLOW	PAINTED FINISHES BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK MG METALLIC GREY YL BRIGHT YELLOW BC BLACK CRINKLE SPECIAL COLOR FINISH SCF _____
NOTES 1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED. 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE				



Phone: 203.775.0172
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice