



d5001

INDUSTROLITE PENDANT

PROJECT: _____
 TYPE: _____
 QUANTITY: _____
 NOTES: _____


SPECIFICATION

| | |
|------------------------|---|
| CONSTRUCTION | Precision-formed aluminum |
| CANOPY | 5" diameter steel canopy |
| MOUNTING | Standard ceiling junction box |
| CORD | White three-conductor cord |
| FINISH | Metal or powder coat paint |
| VOLTAGE | 120V or 277V |
| LIGHT SOURCE | Dedicated LED or medium base socket |
| DIMMING | Non-dimming, 0-10V, ELV, or TRIAC |
| SHADE DIMENSION | 16" diameter x 9" height |
| OVERALL HEIGHT | 60" |
| CODE COMPLIANCE | UL listed, cUL (ETL/ETLc for LED) certified for dry locations |




DIMENSIONS

RELATED PRODUCT: d5000



ORDERING INFORMATION

| MODEL | LAMPING | VOLTAGE | FINISH | OPTIONS |
|---|---|--|---|---|
| <input type="checkbox"/> d5001  | 1M150⁷ 150W MAX, MEDIUM BASE, A TYPE LED8² 8W LED, 736 TOTAL LUMENS LED35² 35W LED, 3500 TOTAL LUMENS | 120¹ 120V 277 277V | METAL FINISHES AL BRUSHED ALUMINUM PA POLISHED ALUMINUM PAINTED FINISHES BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK MG METALLIC GREY YL BRIGHT YELLOW | BHC BLACK, THREE CONDUCTOR CORD CEQ³ CALIFORNIA EARTHQUAKE SWIVEL DIM⁴ DIMMING: 0-10V, ELV, OR TRIAC STEM⁵ RIGID 1/2" DIAMETER STEM EMP⁶ EMERGENCY BATTERY PACK WH WHITE GLOSS T2 MEDIUM TAN AN METALLIC ANTHRACITE SF SEAFOAM MP MAGENTA PINK BZ METALLIC BRONZE SPECIAL COLOR FINISH SCF _____ |
| NOTES 1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE 3. MUST USE RIGID STEM WITH CALIFORNIA EARTHQUAKE SWIVEL 4. SPECIFY DIMMING PROTOCOL 5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH 6. REQUIRES A SEPARATE EM DRIVER THAT MAY AFFECT THE INSTALLATION AND PROFILE OF THE FIXTURE 7. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 8. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE | | | | |



Phone: 203.775.1805
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice