



d5010 INDUSTROLITE PENDANT


PROJECT: _____
 TYPE: _____
 QUANTITY: _____
 NOTES: _____

SPECIFICATION

CONSTRUCTION	Cast-aluminum grill and fittings
DIFFUSER	Clear glass enclosure
CANOPY	5" diameter x 1/2" deep canopy
MOUNTING	Standard wall junction box
STEM⁵	Rigid 1/2" diameter stem standard
FINISH	Metal or powder coat paint
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or medium base socket
DIMENSIONS	14" diameter x 9-3/4" height
OVERALL HEIGHT	34"
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations




DIMENSIONS



RELATED PRODUCT: d1012



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
 <p>d5010</p>	<p>LED6² 6W LED, 552 TOTAL LUMENS</p> <p>1M100⁷ 100W MAX, MEDIUM BASE, A TYPE</p> <p>LED8² 8W LED, 736 TOTAL LUMENS</p>	<p>120¹ 120V</p> <p>277 277V</p>	<p>METAL FINISHES</p> <p>AL BRUSHED ALUMINUM</p> <p>PAINTED FINISHES</p> <p>BG BLACK GLOSS</p> <p>BL METALLIC BLUE</p> <p>RD METALLIC RED</p> <p>CU METALLIC COPPER</p> <p>T1 LIGHT TAN</p> <p>G2 MEDIUM GREY</p> <p>GM METALLIC GREEN</p> <p>MB MATTE BLACK</p> <p>MG METALLIC GREY</p> <p>YL BRIGHT YELLOW</p> <p>BC BLACK CRINKLE</p>	<p>RG³ RIBBED GLASS ENCLOSURE</p> <p>PS³ PERFORATED METAL SLEEVE</p> <p>DIM⁴ DIMMING: 0-10V, ELV, OR TRIAC</p> <p>CEQ CALIFORNIA EARTHQUAKE SWIVEL</p> <p>EMP⁶ EMERGENCY BATTERY PACK</p> <p>WH WHITE GLOSS</p> <p>T2 MEDIUM TAN</p> <p>AN METALLIC ANTHRACITE</p> <p>SF SEAFOAM</p> <p>MP MAGENTA PINK</p> <p>BZ METALLIC BRONZE</p> <p>SPECIAL COLOR FINISH</p> <p>SCF _____</p>
	<p>NOTES</p> <ol style="list-style-type: none"> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED. 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. RIBBED GLASS AND PERFORATED METAL SLEEVE CANNOT BE ORDERED TOGETHER 4. SPECIFY DIMMING PROTOCOL: 0-10V, ELV, OR TRIAC 5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH 6. EMERGENCY BATTERY PACK USES A 12-1/4" DIAMETER CANOPY 7. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 8. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE 			



Phone: 203.775.1805
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice