



# d5012 INDUSTROLITE PENDANT

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_


## SPECIFICATION

<b>CONSTRUCTION</b>	Cast-aluminum grill and fittings
<b>DIFFUSER</b>	Clear glass enclosure
<b>CANOPY</b>	5" diameter x 1/2" deep canopy
<b>MOUNTING</b>	Standard ceiling junction box
<b>STEM<sup>5</sup></b>	Rigid 1/2" diameter stem standard
<b>FINISH</b>	Metal or powder coat paint
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED or medium base socket
<b>DIMENSIONS</b>	17" diameter x 11-3/8" height
<b>OVERALL HEIGHT</b>	34"
<b>CODE COMPLIANCE</b>	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



## DIMENSIONS

## RELATED PRODUCT: d1018



## ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<p>d5012</p>	<p><b>LED8<sup>2</sup></b> 8W LED, 736 TOTAL LUMENS</p> <p><b>1M100<sup>7</sup></b> 100W MAX, MEDIUM BASE, A TYPE</p> <p><b>1M200<sup>7</sup></b> 200W MAX, MEDIUM BASE, A TYPE</p>	<p><b>120<sup>1</sup></b> 120V</p> <p><b>277</b> 277V</p>	<p><b>METAL FINISHES</b></p> <p><b>AL</b> BRUSHED ALUMINUM</p> <p><b>PAINTED FINISHES</b></p> <p><b>BG</b> BLACK GLOSS</p> <p><b>BL</b> METALLIC BLUE</p> <p><b>RD</b> METALLIC RED</p> <p><b>CU</b> METALLIC COPPER</p> <p><b>T1</b> LIGHT TAN</p> <p><b>G2</b> MEDIUM GREY</p> <p><b>GM</b> METALLIC GREEN</p> <p><b>MB</b> MATTE BLACK</p> <p><b>MG</b> METALLIC GREY</p> <p><b>YL</b> BRIGHT YELLOW</p> <p><b>BC</b> BLACK CRINKLE</p>	<p><b>RG<sup>3</sup></b> RIBBED GLASS ENCLOSURE</p> <p><b>PS<sup>3</sup></b> PERFORATED METAL SLEEVE</p> <p><b>DIM<sup>5</sup></b> DIMMING: 0-10V, ELV, OR TRIAC</p> <p><b>CEQ</b> CALIFORNIA EARTHQUAKE SWIVEL</p> <p><b>EMP<sup>6</sup></b> EMERGENCY BATTERY PACK</p> <p><b>WH</b> WHITE GLOSS</p> <p><b>T2</b> MEDIUM TAN</p> <p><b>AN</b> METALLIC ANTHRACITE</p> <p><b>SF</b> SEAFOAM</p> <p><b>MP</b> MAGENTA PINK</p> <p><b>BZ</b> METALLIC BRONZE</p> <p><b>SPECIAL COLOR FINISH</b></p> <p><b>SCF</b> _____</p>
<p><b>NOTES</b></p> <ol style="list-style-type: none"> <li>1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED.</li> <li>2. 3000K IS THE STANDARD COLOR TEMPERATURE</li> <li>3. RIBBED GLASS AND PERFORATED METAL SLEEVE CANNOT BE ORDERED TOGETHER</li> <li>4. SPECIFY DIMMING PROTOCOL: 0-10V, ELV, OR TRIAC</li> <li>5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH</li> <li>6. EMERGENCY BATTERY PACK USES A 12-1/4" DIAMETER CANOPY</li> <li>7. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC</li> <li>8. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE</li> </ol>				



Phone: 203.775.1805  
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

*As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice*