



# d5020

## LEXY PENDANT

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_

### SPECIFICATION

<b>CONSTRUCTION</b>	Acrylic prismatic shade with aluminum components
<b>CANOPY</b>	5" diameter steel canopy
<b>MOUNTING</b>	Standard ceiling junction box
<b>CORD</b>	White three-conductor cord
<b>FINISH</b>	Metal or powder coat paint
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED or medium base socket
<b>DIMENSIONS</b>	12" diameter x 11-1/4" height
<b>OVERALL HEIGHT</b>	60"
<b>CODE COMPLIANCE</b>	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



### DIMENSIONS

### RELATED PRODUCT: d5270



### ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	SHADE COLORS
<input type="checkbox"/> d5020	<b>LED6<sup>2</sup></b> 6W LED, 552 TOTAL LUMENS <b>LED12<sup>2</sup></b> 12W LED, 1104 TOTAL LUMENS <b>1M150<sup>7</sup></b> 150W MAX, MEDIUM BASE, A TYPE	<b>120<sup>1</sup></b> 120V <b>277</b> 277V	<b>METAL FINISHES</b> <b>AL</b> BRUSHED ALUMINUM <b>PA</b> POLISHED ALUMINUM <b>PAINTED FINISHES</b> <b>BG</b> BLACK GLOSS <b>BL</b> METALLIC BLUE <b>RD</b> METALLIC RED <b>CU</b> METALLIC COPPER <b>T1</b> LIGHT TAN <b>G2</b> MEDIUM GREY <b>GM</b> METALLIC GREEN <b>MB</b> MATTE BLACK <b>MG</b> METALLIC GREY <b>WH</b> WHITE GLOSS <b>MP</b> MAGENTA PINK <b>SPECIAL COLOR FINISH</b> <b>SCF</b> _____	<b>CL</b> CLEAR  <b>OPTIONS</b> <b>BLF</b> FLAT ACRYLIC BOTTOM LENS (CLEAR) <b>BLD</b> DOME ACRYLIC BOTTOM LENS (CLEAR) <b>STEM<sup>5</sup></b> RIGID 1/2" DIAMETER STEM <b>DIM<sup>4</sup></b> DIMMING: 0-10V, ELV, OR TRIAC <b>BHC</b> BLACK THREE CONDUCTOR CORD <b>CEQ<sup>3</sup></b> CALIFORNIA EARTHQUAKE SWIVEL <b>EMP<sup>6</sup></b> EMERGENCY BATTERY PACK
<b>NOTES</b> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. MUST USE RIGID STEM WITH CALIFORNIA EARTHQUAKE SWIVEL 4. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC 5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OVERALL HEIGHT 6. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-1/4" DIAMETER CANOPY 7. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 8. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE				



Phone: 203.775.0172  
 P.O. Box 165, 20 Pocono Road, Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice