



# d5021 LEXY PENDANT

PROJECT:  
TYPE:  
QUANTITY:  
NOTES:

---

---

---

---

## SPECIFICATION

<b>CONSTRUCTION</b>	Acrylic prismatic shade with aluminum components
<b>CANOPY</b>	5" diameter steel canopy
<b>MOUNTING</b>	Standard ceiling junction box
<b>CORD</b>	White three-conductor cord
<b>FINISH</b>	Metal or powder coat paint
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED or medium base socket
<b>DIMENSIONS</b>	16" diameter x 15-3/4" height
<b>OVERALL HEIGHT</b>	60"
<b>CODE COMPLIANCE</b>	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



## DIMENSIONS

## RELATED PRODUCT: d5270



## ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	SHADE COLORS
d5021	<b>LED8<sup>2</sup></b> 8W LED, 736 TOTAL LUMENS <b>1M150<sup>7</sup></b> 150W MAX, MEDIUM BASE, A TYPE	<b>120<sup>1</sup></b> 120V <b>277</b> 277V	<b>METAL FINISHES</b> <b>AL</b> BRUSHED ALUMINUM <b>PA</b> POLISHED ALUMINUM <b>PAINTED FINISHES</b> <b>BG</b> BLACK GLOSS <b>BL</b> METALLIC BLUE <b>RD</b> METALLIC RED <b>CU</b> METALLIC COPPER <b>T1</b> LIGHT TAN <b>G2</b> MEDIUM GREY <b>GM</b> METALLIC GREEN <b>MB</b> MATTE BLACK <b>MG</b> METALLIC GREY <b>MB</b> MATTE BLACK <b>MG</b> METALLIC GREY <b>SPECIAL COLOR FINISH</b> <b>SCF</b> _____	<b>CL</b> CLEAR <b>MK</b> MILKY WHITE <b>GR</b> GREEN <b>AM</b> AMBER <b>BL</b> BLUE <b>RD</b> RED
<b>NOTES</b>				
<ol style="list-style-type: none"> <li>1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED.</li> <li>2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K</li> <li>3. MUST USE RIGID STEM WITH CALIFORNIA EARTHQUAKE SWIVEL</li> <li>4. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V, ELV, OR TRIAC</li> <li>5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OVERALL HEIGHT</li> <li>6. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-1/4" DIAMETER CANOPY</li> <li>7. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC</li> <li>8. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE</li> </ol>				
<b>OPTIONS</b>				
<b>BLF</b> FLAT ACRYLIC BOTTOM LENS (CLEAR) <b>BLD</b> DOME ACRYLIC BOTTOM LENS (CLEAR) <b>STEM<sup>5</sup></b> RIGID 1/2" DIAMETER STEM <b>DIM<sup>4</sup></b> DIMMING: 0-10V, ELV, OR TRIAC <b>BHC</b> BLACK THREE CONDUCTOR CORD <b>CEQ<sup>3</sup></b> CALIFORNIA EARTHQUAKE SWIVEL <b>EMP<sup>6</sup></b> EMERGENCY BATTERY PACK				



Phone: 203.775.0172  
 P.O. Box 165, 20 Pocono Road, Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

*As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice*