



d5021

LEXY PENDANT

PROJECT:
TYPE:
QUANTITY:
NOTES:

SPECIFICATION

CONSTRUCTION	Acrylic prismatic shade with aluminum components
CANOPY	5" diameter steel canopy
MOUNTING	Standard ceiling junction box
CORD	White three-conductor cord
FINISH	Metal or powder coat paint
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or medium base socket
DIMENSIONS	16" diameter x 15-3/4" height
OVERALL HEIGHT	60"
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



DIMENSIONS

RELATED PRODUCT: d5270



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	SHADE COLORS
<input type="checkbox"/> d5021	<p>LED8² 8W LED, 736 TOTAL LUMENS</p> <p>LED35² 35W LED, 3500 TOTAL LUMENS</p> <p>1M150⁷ 150W MAX, MEDIUM BASE, A TYPE</p>	<p>120¹ 120V</p> <p>277 277V</p>	<p>METAL FINISHES</p> <p>AL BRUSHED ALUMINUM</p> <p>PA POLISHED ALUMINUM</p> <p>PAINTED FINISHES</p> <p>BG BLACK GLOSS</p> <p>BL METALLIC BLUE</p> <p>RD METALLIC RED</p> <p>CU METALLIC COPPER</p> <p>T1 LIGHT TAN</p> <p>G2 MEDIUM GREY</p> <p>GM METALLIC GREEN</p> <p>MB MATTE BLACK</p> <p>MG METALLIC GREY</p> <p>WH WHITE GLOSS</p> <p>MP MAGENTA PINK</p> <p>SPECIAL COLOR FINISH</p> <p>SCF _____</p>	<p>CL CLEAR</p> <p>MK MILKY WHITE</p> <p>GR GREEN</p> <p>AM AMBER</p> <p>BL BLUE</p> <p>RD RED</p>
NOTES				
<ol style="list-style-type: none"> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. MUST USE RIGID STEM WITH CALIFORNIA EARTHQUAKE SWIVEL 4. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC 5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OVERALL HEIGHT 6. REQUIRES A SEPARATE EM DRIVER THAT MAY AFFECT THE INSTALLATION AND PROFILE OF THE FIXTURE 7. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 8. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE 				
OPTIONS				
<p>BLF FLAT ACRYLIC BOTTOM LENS (CLEAR)</p> <p>BLD DOME ACRYLIC BOTTOM LENS (CLEAR)</p> <p>STEM⁵ RIGID 1/2" DIAMETER STEM</p> <p>DIM⁴ DIMMING: 0-10V, ELV, OR TRIAC</p> <p>BHC BLACK THREE CONDUCTOR CORD</p> <p>CEQ³ CALIFORNIA EARTHQUAKE SWIVEL</p> <p>EMP⁶ EMERGENCY BATTERY PACK</p>				



Phone: 203.775.0172
P.O. Box 165, 20 Pocono Road, Brookfield CT 06804
daLighting.com | cs@daLighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice