



d5027 CORONA PENDANT


PROJECT: _____
 TYPE: _____
 QUANTITY: _____
 NOTES: _____

SPECIFICATION

CONSTRUCTION	Spun-aluminum or solid-copper shade
ACCENTS	Brushed aluminum finial
CANOPY	5" diameter brushed aluminum canopy
MOUNTING	Standard ceiling junction box
CORD	White three-conductor cord
FINISH	Metal or powder coat paint
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or medium base socket
SHADE DIMENSION	9-1/2" diameter, 15" height
OVERALL HEIGHT	60"
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



DIMENSIONS



RELATED PRODUCT: d5026



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5027 	LED8² 8W LED, 736 TOTAL LUMENS 1M100⁶ 100W MAX, MEDIUM BASE, A TYPE	120¹ 120V 277 277V	PAINTED FINISHES BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK MG METALLIC GREY YL BRIGHT YELLOW WH WHITE GLOSS SPECIAL COLOR FINISH SCF _____	INCP⁴ INNER SHADE IN RAW COPPER INCP²⁴ INNER SHADE IN PAINTED COPPER DIM³ DIMMING: 0-10V, ELV, OR TRIAC STEM⁵ RIGID 1/2" DIAMETER STEM TR⁷ FOR USE WITH TRACK SYSTEMS METAL FINISHES AL BRUSHED ALUMINUM PA POLISHED ALUMINUM COPPER FINISHES CPL POLISHED COPPER (LACQUERED) CBL BRUSHED COPPER (LACQUERED) CPU POLISHED COPPER (UNLACQUERED) CBU BRUSHED COPPER (UNLACQUERED)
<p style="text-align: center;">NOTES</p> <ol style="list-style-type: none"> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC 4. STANDARD FIXTURE WITH INNER SHADE PAINTED WHITE 5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH 6. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 7. ADAPTER AND TRACK SUPPLIED BY INSTALLER 8. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE 				



Phone: 203.775.1805
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice