



# d5031 ALANZIA PENDANT

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_

## SPECIFICATION

|                        |   |
|------------------------|---|
| <b>CONSTRUCTION</b>    | Spun-aluminum shade   |
| <b>DIFFUSER</b>        | White opal acrylic diffuser   |
| <b>ACCENTS</b>         | Polished chrome trim, clamps and loops                                  |
| <b>CANOPY</b>          | 5" diameter black canopy  |
| <b>MOUNTING</b>        | Standard ceiling junction box   |
| <b>CORD</b>            | Black, Three-conductor hanging cord<br>Adjustable-height aircraft cable |
| <b>VOLTAGE</b>         | 120V or 277V  |
| <b>LIGHT SOURCE</b>    | Dedicated LED or medium base socket                                     |
| <b>SHADE DIMENSION</b> | 14" diameter x 13-½" height   |
| <b>OVERALL HEIGHT</b>  | 60"   |
| <b>CODE COMPLIANCE</b> | UL listed, cUL (ETL/ETLc for LED) certified for dry locations           |



## DIMENSIONS

## CANOPY:



## ORDERING INFORMATION

| MODEL   | LAMPING   | VOLTAGE  | FINISH  | OPTIONS   |
|---|---|--|---|---|
| <input type="checkbox"/> d5031  | <b>LED12<sup>2</sup></b> 12W LED, 1104 TOTAL LUMENS<br><b>LED16<sup>2</sup></b> 16W LED, 1472 TOTAL LUMENS<br><b>LED35<sup>2</sup></b> 35W LED, 3500 TOTAL LUMENS<br><b>1M150<sup>7</sup></b> 150W MAX, MEDIUM BASE, A TYPE | <b>120<sup>1</sup></b> 120V<br><b>277</b> 277V | <b>PAINTED FINISHES</b><br><b>BG</b> BLACK GLOSS<br><b>BL</b> METALLIC BLUE<br><b>RD</b> METALLIC RED<br><b>CU</b> METALLIC COPPER<br><b>T1</b> LIGHT TAN<br><b>G2</b> MEDIUM GREY<br><b>GM</b> METALLIC GREEN<br><b>MB</b> MATTE BLACK<br><b>MG</b> METALLIC GREY<br><b>YL</b> BRIGHT YELLOW<br><b>WH</b> WHITE GLOSS<br><b>SPECIAL COLOR FINISH</b><br><b>SCF</b> _____ | <b>INCP<sup>3</sup></b> INNER SHADE IN RAW COPPER<br><b>COIL</b> COILED ELECTRICAL CORD<br><b>DIM<sup>4</sup></b> DIMMING: 0-10V, ELV, OR TRIAC<br><b>STEM<sup>5</sup></b> RIGID ½" DIAMETER STEM<br><b>TR<sup>6</sup></b> FOR USE WITH TRACK SYSTEMS<br><br><b>METAL FINISHES</b><br><b>AL</b> BRUSHED ALUMINUM<br><b>PA</b> POLISHED ALUMINUM<br><b>COPPER FINISHES</b><br><b>CPL</b> POLISHED COPPER (LACQUERED)<br><b>CBL</b> BRUSHED COPPER (LACQUERED)<br><b>CPU</b> POLISHED COPPER (UNLACQUERED)<br><b>CBU</b> BRUSHED COPPER (UNLACQUERED) |
| <b>NOTES</b><br>1. FIXTURES ARE FACTORY PREWIRED FOR 120V<br>2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K<br>3. STANDARD FIXTURE WITH INNER SHADE PAINTED WHITE<br>4. SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC<br>5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH<br>6. ADAPTER AND TRACK SUPPLIED BY INSTALLER<br>7. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC<br>8. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REP |   |  |   |   |



Phone: 203.775.1805  
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

*As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice*