



# d5033-MINI

## MINI CLARETA PENDANT

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_

### SPECIFICATION

<b>CONSTRUCTION</b>	Spun-aluminum shade
<b>DIFFUSER</b>	White opal acrylic diffuser
<b>ACCENTS</b>	Polished chrome trim, clamps and loops
<b>CANOPY</b>	5" diameter black canopy
<b>MOUNTING</b>	Standard ceiling junction box
<b>CORD</b>	Black, Three-conductor hanging cord Adjustable-height aircraft cable
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED or medium base socket
<b>SHADE DIMENSION</b>	9-1/2" diameter x 9-1/2" height
<b>OVERALL HEIGHT</b>	60"
<b>CODE COMPLIANCE</b>	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



### DIMENSIONS

### CANOPY:



### ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
d5033-MINI	<p>LED8<sup>2</sup> 8W LED, 736 TOTAL LUMENS</p> <p>1M75<sup>7</sup> 75W MAX, MEDIUM BASE, A TYPE</p>	<p>120<sup>1</sup> 120V</p> <p>277 277V</p>	<p><b>METAL FINISHES</b></p> <p>AL BRUSHED ALUMINUM</p> <p>PA POLISHED ALUMINUM</p> <p><b>PAINTED FINISHES</b></p> <p>BG BLACK GLOSS</p> <p>BL METALLIC BLUE</p> <p>RD METALLIC RED</p> <p>CU METALLIC COPPER</p> <p>T1 LIGHT TAN</p> <p>G2 MEDIUM GREY</p> <p>GM METALLIC GREEN</p> <p>MB MATTE BLACK</p> <p>MG METALLIC GREY</p> <p>YL BRIGHT YELLOW</p>	<p>INCP<sup>3</sup> INNER SHADE IN RAW COPPER</p> <p>COIL COILED ELECTRICAL CORD</p> <p>DIM<sup>4</sup> DIMMING: 0-10V, ELV, OR TRIAC</p> <p>STEM<sup>5</sup> RIGID 1/2" DIAMETER STEM</p> <p>TR<sup>6</sup> FOR USE WITH TRACK SYSTEMS</p> <p>WH WHITE GLOSS</p> <p>T2 MEDIUM TAN</p> <p>AN METALLIC ANTHRACITE</p> <p>SF SEAFOAM</p> <p>MP MAGENTA PINK</p> <p>BZ METALLIC BRONZE</p> <p>SPECIAL COLOR FINISH</p> <p>SCF _____</p>
<p><b>NOTES</b></p> <ol style="list-style-type: none"> <li>1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED.</li> <li>2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K</li> <li>3. FIXTURE COMES STANDARD WITH PAINTED WHITE ON INNER SHADE</li> <li>4. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V, ELV, OR TRIAC</li> <li>5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH</li> <li>6. ADAPTER AND TRACK SUPPLIED BY INSTALLER</li> <li>7. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC</li> <li>8. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE</li> </ol>				



Phone: 203.775.1805  
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

*As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice*