




d5034-MINI

MINI DAVIDO PENDANT

PROJECT:
TYPE:
QUANTITY:
NOTES:

SPECIFICATION

CONSTRUCTION	Spun-aluminum shade
DIFFUSER	White opal acrylic diffuser
ACCENTS	Polished chrome trim, clamps and loops
CANOPY	5" diameter black canopy
MOUNTING	Standard ceiling junction box
CORD	Black, Three-conductor hanging cord Adjustable-height aircraft cable
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or medium base socket
SHADE DIMENSION	9-1/2" diameter, 9-1/2" height
OVERALL HEIGHT	60"
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations




DIMENSIONS

CANOPY:



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5034-MINI	<p>LED8² 8W LED, 736 TOTAL LUMENS</p> <p>1M75⁷ 75W MAX, MEDIUM BASE, A TYPE</p>	<p>120¹ 120V</p> <p>277 277V</p>	<p>METAL FINISHES</p> <p>AL BRUSHED ALUMINUM</p> <p>PA POLISHED ALUMINUM</p> <p>PAINTED FINISHES</p> <p>BG BLACK GLOSS</p> <p>BL METALLIC BLUE</p> <p>RD METALLIC RED</p> <p>CU METALLIC COPPER</p> <p>T1 LIGHT TAN</p> <p>G2 MEDIUM GREY</p> <p>GM METALLIC GREEN</p> <p>MB MATTE BLACK</p> <p>MG METALLIC GREY</p> <p>YL BRIGHT YELLOW</p>	<p>INCP³ INNER SHADE IN RAW COPPER⁴</p> <p>COIL COILED ELECTRICAL CORD</p> <p>DIM⁴ DIMMING: 0-10V, ELV, OR TRIAC</p> <p>STEM⁵ RIGID 1/2" DIAMETER STEM</p> <p>TR⁶ FOR USE WITH TRACK SYSTEMS</p> <p>WH WHITE GLOSS</p> <p>T2 MEDIUM TAN</p> <p>AN METALLIC ANTHRACITE</p> <p>SF SEAFOAM</p> <p>MP MAGENTA PINK</p> <p>BZ METALLIC BRONZE</p> <p>SPECIAL COLOR FINISH</p> <p>SCF _____</p>
<p align="center">NOTES</p> <ol style="list-style-type: none"> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. STANDARD FIXTURE WITH INNER SHADE PAINTED WHITE 4. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC 5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OVERALL HEIGHT 6. ADAPTER AND TRACK SUPPLIED BY INSTALLER 7. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 8. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE 				



Phone: 203.775.1805
P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice