



d5037 BARSTOW PENDANT

PROJECT:
TYPE:
QUANTITY:
NOTES:

SPECIFICATION

CONSTRUCTION	Spun-aluminum or solid-copper shade
DIFFUSER	White opal acrylic diffuser
ACCENTS	Polished chrome trim, clamps and loops
CANOPY	5" diameter black canopy
MOUNTING	Standard ceiling junction box
CORD	Black, Three-conductor hanging cord Adjustable-height aircraft cable
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or medium base socket
SHADE DIMENSION	14" diameter x 16-1/2" height
OVERALL HEIGHT	60"
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



DIMENSIONS

CANOPY:



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5037	<p>LED12² 12W LED, 1104 TOTAL LUMENS</p> <p>LED16² 16W LED, 1472 TOTAL LUMENS</p> <p>LED35² 35W LED, 3500 TOTAL LUMENS</p> <p>1M150⁷ 150W MAX, MEDIUM BASE, A TYPE</p>	<p>120¹ 120V</p> <p>277 277V</p>	<p>PAINTED FINISHES</p> <p>BG BLACK GLOSS</p> <p>BL METALLIC BLUE</p> <p>RD METALLIC RED</p> <p>CU METALLIC COPPER</p> <p>T1 LIGHT TAN</p> <p>G2 MEDIUM GREY</p> <p>GM METALLIC GREEN</p> <p>MB MATTE BLACK</p> <p>MG METALLIC GREY</p> <p>YL BRIGHT YELLOW</p> <p>WH WHITE GLOSS</p> <p>SPECIAL COLOR FINISH</p> <p>SCF _____</p>	<p>INCP³ INNER SHADE IN RAW COPPER</p> <p>COIL COILED ELECTRICAL CORD</p> <p>DIM⁴ DIMMING: 0-10V, ELV, OR TRIAC</p> <p>STEM⁵ RIGID 1/2" DIAMETER STEM</p> <p>TR⁶ FOR USE WITH TRACK SYSTEMS</p> <p>METAL FINISHES</p> <p>AL BRUSHED ALUMINUM</p> <p>PA POLISHED ALUMINUM</p> <p>COPPER FINISHES</p> <p>CPL POLISHED COPPER (LACQUERED)</p> <p>CBL BRUSHED COPPER (LACQUERED)</p> <p>CPU POLISHED COPPER (UNLACQUERED)</p> <p>CBU BRUSHED COPPER (UNLACQUERED)</p>
<p>NOTES</p> <ol style="list-style-type: none"> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. STANDARD FIXTURE WITH INNER SHADE PAINTED WHITE 4. SPECIFY DIMMING PROTOCOL: 0-10V, ELV, OR TRIAC 5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH 6. ADAPTER AND TRACK SUPPLIED BY INSTALLER 7. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 8. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REP 				



Phone: 203.775.1805
P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice