



# d5038

## BAYARD PENDANT

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_

### SPECIFICATION

<b>CONSTRUCTION</b>	Spun-aluminum or solid-copper shade
<b>DIFFUSER</b>	White opal acrylic diffuser
<b>ACCENTS</b>	Polished chrome trim, clamps and loops
<b>CANOPY</b>	5" diameter black canopy
<b>MOUNTING</b>	Standard ceiling junction box
<b>CORD</b>	Black, Three-conductor hanging cord Adjustable-height aircraft cable
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED or medium base socket
<b>SHADE DIMENSION</b>	14" diameter x 17" height
<b>OVERALL HEIGHT</b>	60"
<b>CODE COMPLIANCE</b>	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



### DIMENSIONS

### CANOPY:



### ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5038	<p><b>LED12<sup>2</sup></b> 12W LED, 1104 TOTAL LUMENS</p> <p><b>LED16<sup>2</sup></b> 16W LED, 1472 TOTAL LUMENS</p> <p><b>LED35<sup>2</sup></b> 35W LED, 3500 TOTAL LUMENS</p> <p><b>1M150<sup>7</sup></b> 150W MAX, MEDIUM BASE, A TYPE</p>	<p><b>120<sup>1</sup></b> 120V</p> <p><b>277</b> 277V</p>	<p><b>PAINTED FINISHES</b></p> <p><b>BG</b> BLACK GLOSS</p> <p><b>BL</b> METALLIC BLUE</p> <p><b>RD</b> METALLIC RED</p> <p><b>CU</b> METALLIC COPPER</p> <p><b>T1</b> LIGHT TAN</p> <p><b>G2</b> MEDIUM GREY</p> <p><b>GM</b> METALLIC GREEN</p> <p><b>MB</b> MATTE BLACK</p> <p><b>MG</b> METALLIC GREY</p> <p><b>YL</b> BRIGHT YELLOW</p> <p><b>WH</b> WHITE GLOSS</p> <p><b>SPECIAL COLOR FINISH</b></p> <p><b>SCF</b> _____</p>	<p><b>INCP<sup>3</sup></b> INNER SHADE IN RAW COPPER</p> <p><b>COIL</b> COILED ELECTRICAL CORD</p> <p><b>DIM<sup>4</sup></b> DIMMING: 0-10V, ELV, OR TRIAC</p> <p><b>STEM<sup>5</sup></b> RIGID 1/2" DIAMETER STEM</p> <p><b>TR<sup>6</sup></b> FOR USE WITH TRACK SYSTEMS</p> <p><b>METAL FINISHES</b></p> <p><b>AL</b> BRUSHED ALUMINUM</p> <p><b>PA</b> POLISHED ALUMINUM</p> <p><b>COPPER FINISHES</b></p> <p><b>CPL</b> POLISHED COPPER (LACQUERED)</p> <p><b>CBL</b> BRUSHED COPPER (LACQUERED)</p> <p><b>CPU</b> POLISHED COPPER (UNLACQUERED)</p> <p><b>CBU</b> BRUSHED COPPER (UNLACQUERED)</p>
<p><b>NOTES</b></p> <ol style="list-style-type: none"> <li>1. FIXTURES ARE FACTORY PREWIRED FOR 120V</li> <li>2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K</li> <li>3. STANDARD FIXTURE WITH INNER SHADE PAINTED WHITE</li> <li>4. SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC</li> <li>5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH</li> <li>6. ADAPTER AND TRACK SUPPLIED BY INSTALLER</li> <li>7. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC</li> <li>8. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REP</li> </ol>				



Phone: 203.775.1805  
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

*As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice*