



# d5038 BAYARD PENDANT

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_

## SPECIFICATION

<b>CONSTRUCTION</b>	Spun-aluminum or solid-copper shade
<b>DIFFUSER</b>	White opal acrylic diffuser
<b>ACCENTS</b>	Polished chrome trim, clamps and loops
<b>CANOPY</b>	5" diameter black canopy
<b>MOUNTING</b>	Standard ceiling junction box
<b>CORD</b>	Black, Three-conductor hanging cord Adjustable-height aircraft cable
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED or medium base socket
<b>SHADE DIMENSION</b>	14" diameter x 17" height
<b>OVERALL HEIGHT</b>	60"
<b>CODE COMPLIANCE</b>	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



## DIMENSIONS

## CANOPY:



## ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5038	<b>LED12<sup>2</sup></b> 12W LED, 1104 TOTAL LUMENS <b>LED16<sup>2</sup></b> 16W LED, 1472 TOTAL LUMENS <b>LED35<sup>2</sup></b> 35W LED, 3500 TOTAL LUMENS <b>1M150<sup>7</sup></b> 150W MAX, MEDIUM BASE, A TYPE	<b>120<sup>1</sup></b> 120V <b>277</b> 277V	<b>PAINTED FINISHES</b> <b>BG</b> BLACK GLOSS <b>BL</b> METALLIC BLUE <b>RD</b> METALLIC RED <b>CU</b> METALLIC COPPER <b>T1</b> LIGHT TAN <b>G2</b> MEDIUM GREY <b>GM</b> METALLIC GREEN <b>MB</b> MATTE BLACK <b>MG</b> METALLIC GREY <b>YL</b> BRIGHT YELLOW <b>WH</b> WHITE GLOSS <b>SPECIAL COLOR FINISH</b> <b>SCF</b> _____	<b>INCP<sup>3</sup></b> INNER SHADE IN RAW COPPER <b>COIL</b> COILED ELECTRICAL CORD <b>DIM<sup>4</sup></b> DIMMING: 0-10V, ELV, OR TRIAC <b>STEM<sup>5</sup></b> RIGID 1/2" DIAMETER STEM <b>TR<sup>6</sup></b> FOR USE WITH TRACK SYSTEMS  <b>METAL FINISHES</b> <b>AL</b> BRUSHED ALUMINUM <b>PA</b> POLISHED ALUMINUM <b>COPPER FINISHES</b> <b>CPL</b> POLISHED COPPER (LACQUERED) <b>CBL</b> BRUSHED COPPER (LACQUERED) <b>CPU</b> POLISHED COPPER (UNLACQUERED) <b>CBU</b> BRUSHED COPPER (UNLACQUERED)
<b>NOTES</b> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. STANDARD FIXTURE WITH INNER SHADE PAINTED WHITE 4. SPECIFY DIMMING PROTOCOL: 0-10V, ELV, OR TRIAC 5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH 6. ADAPTER AND TRACK SUPPLIED BY INSTALLER 7. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 8. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REP				



Phone: 203.775.1805  
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

*As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice*