



# d5237 BASIX PENDANT

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_


## SPECIFICATION

<b>CONSTRUCTION</b>	Aluminum shade and canopy
<b>DIFFUSER</b>	White opal acrylic bottom lens
<b>CANOPY</b>	5" diameter black canopy
<b>MOUNTING</b>	Standard ceiling junction box
<b>CORD</b>	Black, Three-conductor hanging cord Adjustable-height aircraft cable
<b>FINISH</b>	Metal or powder coat paint
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED or medium base socket
<b>SHADE DIMENSION</b>	7-1/4" diameter x 8-1/4" height
<b>OVERALL HEIGHT</b>	60"
<b>CODE COMPLIANCE</b>	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



## DIMENSIONS

## CANOPY:



## ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5237	<b>LED8<sup>2</sup></b> 8W LED, 736 TOTAL LUMENS <b>1M75<sup>6</sup></b> 75W MAX, MEDIUM BASE, A TYPE	<b>120<sup>1</sup></b> 120V <b>277</b> 277V	<b>METAL FINISHES</b> <b>AL</b> BRUSHED ALUMINUM <b>PAINTED FINISHES</b> <b>BG</b> BLACK GLOSS <b>BL</b> METALLIC BLUE <b>RD</b> METALLIC RED <b>CU</b> METALLIC COPPER <b>T1</b> LIGHT TAN <b>G2</b> MEDIUM GREY <b>GM</b> METALLIC GREEN <b>MB</b> MATTE BLACK <b>MG</b> METALLIC GREY <b>YL</b> BRIGHT YELLOW <b>BC</b> BLACK CRINKLE	<b>COIL</b> COILED ELECTRIC CORD <b>DIM<sup>3</sup></b> DIMMING: 0-10V, ELV, OR TRIAC <b>STEM<sup>4</sup></b> RIGID 1/2" DIAMETER STEM <b>EMP<sup>5</sup></b> EMERGENCY BATTERY PACK  <b>WH</b> WHITE GLOSS <b>T2</b> MEDIUM TAN <b>AN</b> METALLIC ANTHRACITE <b>SF</b> SEAFOAM <b>MP</b> MAGENTA PINK <b>BZ</b> METALLIC BRONZE <b>SPECIAL COLOR FINISH</b> <b>SCF</b> _____
<b>NOTES</b> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC 4. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OVERALL HEIGHT 5. REQUIRES A SEPARATE EM DRIVER THAT MAY AFFECT THE INSTALLATION AND PROFILE OF THE FIXTURE 6. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 7. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE				



Phone: 203.775.1805  
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice