



d5243

MERIDIAN PENDANT

PROJECT: _____
 TYPE: _____
 QUANTITY: _____
 NOTES: _____

SPECIFICATION

CONSTRUCTION	Aluminum shade and canopy
DIFFUSER	White opal acrylic bottom lens
ACCENTS	Brushed aluminum buttons
CANOPY	5" diameter black canopy
MOUNTING	Standard ceiling junction box
CORD	Black, Three-conductor hanging cord Adjustable-height aircraft cable
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or medium base socket
OVERALL HEIGHT	60"
SHADE DIMENSION	16-3/4" diameter x 8-1/2" height
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



DIMENSIONS



CANOPY:



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5243	LED12² 12W LED, 1104DELIVERED LUMENS 1M100⁶ 100W MAX, MEDIUM BASE, A TYPE	120¹ 120V 277 277V	METAL FINISHES AL BRUSHED ALUMINUM PAINTED FINISHES BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK MG METALLIC GREY YL BRIGHT YELLOW BC BLACK CRINKLE	COIL COILED ELECTRIC CORD DIM³ DIMMING: 0-10V, ELV, OR TRIAC STEM⁴ RIGID 1/2" DIAMETER STEM EMP⁵ EMERGENCY BATTERY PACK WH WHITE GLOSS T2 MEDIUM TAN AN METALLIC ANTHRACITE SF SEAFOAM MP MAGENTA PINK BZ METALLIC BRONZE SPECIAL COLOR FINISH SCF _____
<p align="center">NOTES</p> <ol style="list-style-type: none"> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC 4. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OVERALL HEIGHT 5. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-1/4" DIAMETER CANOPY 6. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 7. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE 				



Phone: 203.775.1805
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice