



# d5250

## ARENA PENDANT


PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_

### SPECIFICATION

<b>CONSTRUCTION</b>	Spun-aluminum shade
<b>OPTIONAL DIFFUSER</b>	Optional white opal acrylic diffuser with center aperture
<b>ACCENTS</b>	Brushed aluminum standoffs and knobs
<b>CANOPY</b>	5" diameter brushed aluminum canopy
<b>MOUNTING</b>	Standard ceiling junction box
<b>STEM<sup>5</sup></b>	Rigid 1/2" diameter stem
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED or medium base socket
<b>SHADE DIMENSION</b>	18" diameter x 13" height
<b>OVERALL HEIGHT</b>	38"
<b>CODE COMPLIANCE</b>	UL listed, cUL (ETL/ETLc for LED) certified for dry locations




### DIMENSIONS



### CANOPY:



### ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5250 	<b>LED12<sup>2</sup></b> 12W LED, 1104 TOTAL LUMENS <b>LED35<sup>2</sup></b> 35W LED, 3500 TOTAL LUMENS <b>1M150<sup>7</sup></b> 150W MAX, MEDIUM BASE, A TYPE	<b>120<sup>1</sup></b> 120V <b>277</b> 277V	<b>METAL FINISHES</b> <b>AL</b> BRUSHED ALUMINUM <b>PA</b> POLISHED ALUMINUM <b>PAINTED FINISHES</b> <b>BG</b> BLACK GLOSS <b>BL</b> METALLIC BLUE <b>RD</b> METALLIC RED <b>CU</b> METALLIC COPPER <b>T1</b> LIGHT TAN <b>G2</b> MEDIUM GREY <b>GM</b> METALLIC GREEN <b>MB</b> MATTE BLACK <b>MG</b> METALLIC GREY <b>YL</b> BRIGHT YELLOW	<b>DISC<sup>3</sup></b> WHITE OPAL ACRYLIC DISK <sup>4</sup> <b>CPI</b> CUSTOM PAINTED INTERIOR <b>DIM<sup>4</sup></b> DIMMING: 0-10V, ELV, OR TRIAC <b>EMP<sup>6</sup></b> EMERGENCY BATTERY PACK <b>WH</b> WHITE GLOSS <b>T2</b> MEDIUM TAN <b>AN</b> METALLIC ANTHRACITE <b>SF</b> SEAFOAM <b>MP</b> MAGENTA PINK <b>BZ</b> METALLIC BRONZE <b>SPECIAL COLOR FINISH</b> <b>SCF</b> _____
<p align="center"><b>NOTES</b></p> <ol style="list-style-type: none"> <li>1. FIXTURES ARE FACTORY PREWIRED FOR 120V</li> <li>2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K</li> <li>3. WHITE OPAL ACRYLIC DISK WITH CENTER APERTURE WITH BRUSHED ALUMINUM STANDOFFS AND KNOBS. 21" DIAMETER</li> <li>4. SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC</li> <li>5. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH</li> <li>6. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-1/4" DIAMETER CANOPY</li> <li>7. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC</li> <li>8. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REP</li> </ol>				



Phone: 203.775.1805  
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice