



# d5260

## MINI DIVA PENDANT

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_


\_\_\_\_\_

### SPECIFICATION

<b>CONSTRUCTION</b>	Spun-aluminum shade
<b>CANOPY</b>	5" diameter canopy in same finish as cap
<b>MOUNTING</b>	Standard ceiling junction box
<b>CORD</b>	Clear silver hanging cord
<b>FINISH</b>	Metal or powder coat paint
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED
<b>SHADE DIMENSION</b>	4- <sup>1</sup> / <sub>8</sub> " diameter x 6- <sup>1</sup> / <sub>2</sub> " height
<b>OVERALL HEIGHT</b>	60"
<b>CODE COMPLIANCE</b>	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



### DIMENSIONS



### RELATED PRODUCT: d5265



### ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	CAP FINISHES	FINISH
<input type="checkbox"/> d5260-MINI 	<b>LED6<sup>2</sup></b> 6W LED WITH ELECTRONIC DRIVER	<b>120<sup>1</sup></b> 120V <b>277</b> 277V	<b>PC</b> POLISHED CHROME <b>SC</b> SATIN CHROME <b>PB</b> POLISHED BRASS <b>BB</b> BRUSHED BRASS	<b>METAL FINISHES</b> <b>AL</b> BRUSHED ALUMINUM <b>PA</b> POLISHED ALUMINUM <b>PAINTED FINISHES</b> <b>BG</b> BLACK GLOSS <b>BL</b> METALLIC BLUE <b>RD</b> METALLIC RED <b>CU</b> METALLIC COPPER <b>T1</b> LIGHT TAN <b>G2</b> MEDIUM GREY <b>GM</b> METALLIC GREEN <b>MB</b> MATTE BLACK <b>SPECIAL COLOR FINISH</b> <b>SCF</b> _____
<b>NOTES</b> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC 4. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OVERALL HEIGHT 5. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12- <sup>1</sup> / <sub>4</sub> " DIAMETER CANOPY 6. ADAPTER AND TRACK SUPPLIED BY INSTALLER 7. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE		<b>OPTIONS</b> <b>DIM<sup>3</sup></b> DIMMING: 0-10V, ELV, OR TRIAC <b>STEM<sup>4</sup></b> RIGID <sup>1</sup> / <sub>2</sub> " DIAMETER STEM <b>TR<sup>6</sup></b> FOR USE WITH TRACK SYSTEMS <b>EMP<sup>5</sup></b> EMERGENCY BATTERY PACK		



Phone: 203.775.1805  
 P.O. Box 165, 20 Pocono Road, Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

*As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice*