



# d5261

## DEBUTANTE PENDANT


PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_

### SPECIFICATION

<b>CONSTRUCTION</b>	Spun-aluminum shade
<b>CANOPY</b>	5" diameter canopy in same finish as cap
<b>MOUNTING</b>	Standard ceiling junction box
<b>CORD</b>	Clear silver hanging cord
<b>FINISH</b>	Metal or powder coat paint
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED
<b>SHADE DIMENSION</b>	6" diameter x 4-1/2" height
<b>OVERALL HEIGHT</b>	60"
<b>CODE COMPLIANCE</b>	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



### DIMENSIONS



### RELATED PRODUCT: d5260



### ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	CAP FINISHES	FINISH
d5261	LED6 <sup>2</sup> 6W LED WITH ELECTRONIC DRIVER	120 <sup>1</sup> 120V 277 277V	PC POLISHED CHROME SC SATIN CHROME PB POLISHED BRASS BB BRUSHED BRASS	METAL FINISHES AL BRUSHED ALUMINUM PA POLISHED ALUMINUM PAINTED FINISHES BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK SPECIAL COLOR FINISH SCF _____
<b>NOTES</b>				
1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC 4. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OVERALL HEIGHT 5. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-1/4" DIAMETER CANOPY 6. ADAPTER AND TRACK SUPPLIED BY INSTALLER 7. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE				
<b>OPTIONS</b>				
DIM <sup>3</sup> DIMMING: 0-10V, ELV, OR TRIAC STEM <sup>4</sup> RIGID 1/2" DIAMETER STEM TR <sup>6</sup> FOR USE WITH TRACK SYSTEMS EMP <sup>5</sup> EMERGENCY BATTERY PACK				



Phone: 203.775.1805  
 P.O. Box 165, 20 Pocono Road, Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

*As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice*