



d5265 DIVA PENDANT


PROJECT: _____
 TYPE: _____
 QUANTITY: _____
 NOTES: _____

SPECIFICATION

CONSTRUCTION	Spun-aluminum
TOP CAP	Polished or brushed chrome, brass
CANOPY	5" diameter canopy in same finish as cap
MOUNTING	Standard ceiling junction box
CORD	Clear silver hanging cord
FINISH	Metal or powder coat paint
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED
SHADE DIMENSION	8-1/2" diameter x 13-1/2" height
OVERALL HEIGHT	60"
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



DIMENSIONS



RELATED PRODUCT: d5260



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	CAP FINISHES	FINISH
d5265 	LED8² 8W LED WITH ELECTRONIC DRIVER LED12² 12W LED WITH ELECTRONIC DRIVER	120¹ 120V 277 277V	PC POLISHED CHROME SC SATIN CHROME PB POLISHED BRASS BB BRUSHED BRASS	METAL FINISHES AL BRUSHED ALUMINUM PA POLISHED ALUMINUM PAINTED FINISHES BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK SPECIAL COLOR FINISH SCF _____
	NOTES 1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED. 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V, ELV, OR TRIAC 4. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OVERALL HEIGHT 5. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-1/4" DIAMETER CANOPY 6. ADAPTER AND TRACK SUPPLIED BY INSTALLER 7. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE		OPTIONS DIM³ DIMMING: 0-10V, ELV, OR TRIAC STEM⁴ RIGID 1/2" DIAMETER STEM TR⁶ FOR USE WITH TRACK SYSTEMS EMP⁵ EMERGENCY BATTERY PACK	



Phone: 203.775.1805
 P.O. Box 165, 20 Pocono Road, Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice