



d5270 DOME PENDANT

PROJECT: _____
 TYPE: _____
 QUANTITY: _____
 NOTES: _____

SPECIFICATION


CONSTRUCTION	Clear acrylic prismatic shade
CANOPY	5" diameter canopy with perforated metal disc
BALLAST	Ballast located in perforated housing above shade
MOUNTING	Standard wall junction box
CORD	Adjustable-height, aircraft cable supports fixture
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or medium base socket
SHADE DIMENSION	12" diameter x 11-3/4" height
OVERALL HEIGHT	60"
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



DIMENSIONS



CANOPY:



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	SHADE COLORS
d5270	LED8² 8W LED, 736 TOTAL LUMENS 1M150⁵ 150W MAX, MEDIUM BASE, A TYPE	120¹ 120V 277 277V	METAL FINISHES AL BRUSHED ALUMINUM PAINTED FINISHES BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK MG METALLIC GREY SPECIAL COLOR FINISH SCF _____	CL CLEAR MK MILKY WHITE GR GREEN AM AMBER BL BLUE RD RED
NOTES				
<ol style="list-style-type: none"> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED. 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OVERALL HEIGHT 4. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-1/4" DIAMETER CANOPY 5. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 6. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE 				
OPTIONS				
BLF FLAT ACRYLIC BOTTOM LENS (CLEAR) BLDC DOME ACRYLIC BOTTOM LENS (CLEAR) STEM³ RIGID 1/2" DIAMETER STEM EMP⁴ EMERGENCY BATTERY PACK				



Phone: 203.775.1805
 P.O. Box 165, 20 Pocono Road, Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice