d5292
SFUMATO PENDANT

PROJECT:
TYPE:
QUANTITY:
NOTES:

SPECIFICATION

CONSTRUCTION	Italian hand-blown glass shade
CANOPY	5″ domed polished aluminum canopy
MOUNTING	Standard ceiling junction box
CORD	Fixture suspended with a clear electrical cord
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or medium base socket
DIMMING	Non-dimming, 0-10V, ELV, or TRIAC
SHADE DIMENSION	5″ diameter x 17-½″ height
OVERALL HEIGHT	71″
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations

DIMENSIONS



CANOPY:

ORDERING INFORMATION

MODEL

- ☐ d5292

LAMPING

- ☐ LED8[2] 8W LED WITH ELECTRONIC DRIVER
- ☐ 1M60[3] 60W MAX, MEDIUM BASE, T-10 TYPE

VOLTAGE

- ☐ 120[1] 120V
- ☐ 277 277V

GLASS FINISH

- ☐ WO WHITE OPAL

OPTIONS

- ☐ PC POLISHED CHROME

NOTES

1. FIXTURES ARE FACTORY PREWIRED FOR 120V
2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K
3. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC
4. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE

Phone: 203.775.1805
P.O. Box 165, 20 Pocono Road, Brookfield CT 06804
dacLighting.com | cs@dacLighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice