



d5292

SFUMATO PENDANT


PROJECT: _____
 TYPE: _____
 QUANTITY: _____
 NOTES: _____

SPECIFICATION

CONSTRUCTION	Italian hand-blown glass shade
CANOPY	5" domed polished aluminum canopy
MOUNTING	Standard ceiling junction box
CORD	Fixture suspended with a clear electrical cord
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or medium base socket
DIMMING	Non-dimming, 0-10V, ELV, or TRIAC
SHADE DIMENSION	5" diameter x 17-1/2" height
OVERALL HEIGHT	71"
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



DIMENSIONS



CANOPY:



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	GLASS FINISH	OPTIONS
<input type="checkbox"/> d5292	LED8² 8W LED WITH ELECTRONIC DRIVER 1M60³ 60W MAX, MEDIUM BASE, T-10 TYPE	120¹ 120V 277 277V	WO WHITE OPAL	PC POLISHED CHROME
NOTES 1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 4. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE				



Phone: 203.775.1805
 P.O. Box 165, 20 Pocono Road, Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice