



# d5403 / d5404

## COTEAU PENDANT


PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_

### SPECIFICATION


<b>CONSTRUCTION</b>	Spun-aluminum or solid-copper shade
<b>DIFFUSER</b>	White opal acrylic diffuser
<b>ACCENTS</b>	Polished chrome trim, clamps and loops
<b>CANOPY</b>	5" diameter black canopy
<b>MOUNTING</b>	Standard ceiling junction box
<b>CORD</b>	Black, Three-conductor hanging cord Adjustable-height aircraft cable
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED or medium base socket
<b>SHADE DIMENSION</b>	12" diameter x 19" height
<b>OVERALL HEIGHT</b>	60"
<b>CODE COMPLIANCE</b>	UL listed, cUL (ETL/ETLc for LED) certified for dry locations





### d5403 DIMENSIONS



### d5404 DIMENSIONS



### ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5403 	<b>LED12<sup>2</sup></b> 8W LED PRIMARY LIGHT SOURCE <sup>4</sup> <b>LED16<sup>2</sup></b> 12W LED PRIMARY LIGHT SOURCE <sup>4</sup> <b>1N100<sup>8</sup></b> ONE 100W MEDIUM BASE, A TYPE	<b>120<sup>1</sup></b> 120V <b>277</b> 277V	<b>PAINTED FINISHES</b> <b>BG</b> BLACK GLOSS <b>BL</b> METALLIC BLUE <b>RD</b> METALLIC RED <b>CU</b> METALLIC COPPER <b>T1</b> LIGHT TAN <b>G2</b> MEDIUM GREY <b>GM</b> METALLIC GREEN <b>MB</b> MATTE BLACK <b>MG</b> METALLIC GREY <b>YL</b> BRIGHT YELLOW <b>WH</b> WHITE GLOSS <b>SPECIAL COLOR FINISH</b> <b>SCF</b> _____	<b>INCP<sup>3</sup></b> INNER SHADE IN RAW COPPER <b>COIL</b> COILED ELECTRICAL CORD <b>DIM<sup>5</sup></b> DIMMING: 0-10V, ELV, OR TRIAC <b>STEM<sup>6</sup></b> RIGID 1/2" DIAMETER STEM <b>ISW<sup>7</sup></b> INDEPENDENT SWITCHING  <b>METAL FINISHES</b> <b>AL</b> BRUSHED ALUMINUM <b>PA</b> POLISHED ALUMINUM <b>COPPER FINISHES</b> <b>CPL</b> POLISHED COPPER (LACQUERED) <b>CBL</b> BRUSHED COPPER (LACQUERED) <b>CPU</b> POLISHED COPPER (UNLACQUERED) <b>CBU</b> BRUSHED COPPER (UNLACQUERED)
<input type="checkbox"/> d5404 	<p style="text-align: center;"><b>NOTES</b></p> <ol style="list-style-type: none"> <li>1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED</li> <li>2. 3000K IS THE STANDARD COLOR TEMPERATURE</li> <li>3. STANDARD FIXTURE WITH INNER SHADE PAINTED WHITE</li> <li>4. PERFORATED DECORATIVE CHAMBER LIT BY A 4W LED MODULE.</li> <li>5. SPECIFY DIMMING PROTOCOL: 0-10V, ELV, OR TRIAC</li> <li>6. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH</li> <li>7. INDEPENDENT SWITCHING OF ACCENT LIGHT AND DOWNLIGHT</li> <li>8. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC</li> <li>9. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE</li> </ol>			



Phone: 203.775.1805  
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

*As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice*