



# d5405 / d5406

## COTEAU PENDANT


PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_

### SPECIFICATION


<b>CONSTRUCTION</b>	Spun-aluminum or solid-copper shade
<b>DIFFUSER</b>	White opal acrylic diffuser
<b>ACCENTS</b>	Polished chrome trim, clamps and loops
<b>CANOPY</b>	5" diameter black canopy
<b>MOUNTING</b>	Standard ceiling junction box
<b>CORD</b>	Black, Three-conductor hanging cord Adjustable-height aircraft cable
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED
<b>SHADE DIMENSION</b>	19-1/2" diameter x 31" height
<b>OVERALL HEIGHT</b>	60"
<b>CODE COMPLIANCE</b>	UL listed, cUL (ETL/ETLc for LED) certified for dry locations





### d5405 DIMENSIONS



### d5406 DIMENSIONS



### ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5405 	<b>LED20<sup>2</sup></b> 20W LED PRIMARY LIGHT SOURCE <sup>4</sup> <b>LED28<sup>2</sup></b> 28W LED PRIMARY LIGHT SOURCE <sup>4</sup> <b>LED35<sup>2</sup></b> 35W LED PRIMARY LIGHT SOURCE <sup>4</sup> <b>LED40<sup>2</sup></b> 40W LED PRIMARY LIGHT SOURCE <sup>4</sup>	<b>120<sup>1</sup></b> 120V <b>277</b> 277V	<b>PAINTED FINISHES</b> <b>BG</b> BLACK GLOSS <b>BL</b> METALLIC BLUE <b>RD</b> METALLIC RED <b>CU</b> METALLIC COPPER <b>T1</b> LIGHT TAN <b>G2</b> MEDIUM GREY <b>GM</b> METALLIC GREEN <b>MB</b> MATTE BLACK <b>MG</b> METALLIC GREY <b>YL</b> BRIGHT YELLOW <b>WH</b> WHITE GLOSS <b>SPECIAL COLOR FINISH</b> <b>SCF</b> _____	<b>INCP<sup>3</sup></b> INNER SHADE IN RAW COPPER <b>COIL</b> COILED ELECTRICAL CORD <b>DIM<sup>5</sup></b> DIMMING: 0-10V, ELV, OR TRIAC <b>STEM<sup>6</sup></b> RIGID 1/2" DIAMETER STEM <b>ISW<sup>7</sup></b> INDEPENDENT SWITCHING  <b>METAL FINISHES</b> <b>AL</b> BRUSHED ALUMINUM <b>PA</b> POLISHED ALUMINUM <b>COPPER FINISHES</b> <b>CPL</b> POLISHED COPPER (LACQUERED) <b>CBL</b> BRUSHED COPPER (LACQUERED) <b>CPU</b> POLISHED COPPER (UNLACQUERED) <b>CBU</b> BRUSHED COPPER (UNLACQUERED)
<input type="checkbox"/> d5406 	<b>NOTES</b> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED 2. 3000K IS THE STANDARD COLOR TEMPERATURE 3. STANDARD FIXTURE WITH INNER SHADE PAINTED WHITE 4. PERFORATED DECORATIVE CHAMBER LIT BY A 4W LED MODULE. 5. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V, ELV, OR TRIAC 6. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH 7. INDEPENDENT SWITCHING OF ACCENT LIGHT AND DOWNLIGHT 8. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REP			



Phone: 203.775.1805  
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

*As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice*