



d5407

BELLA PENDANT


PROJECT: _____
 TYPE: _____
 QUANTITY: _____
 NOTES: _____

SPECIFICATION

CONSTRUCTION	Precision-formed aluminum shade with clear glass enclosure and cast aluminum grill and fittings
CANOPY	5" diameter black canopy
MOUNTING	Standard ceiling junction box
CORD	Black, Three-conductor hanging cord Adjustable-height aircraft cable
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED
SHADE DIMENSION	19" diameter x 13" height
OVERALL HEIGHT	60"
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



DIMENSIONS



CANOPY:



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5407 	LED8² 8W LED WITH ELECTRONIC DRIVER	120¹ 120V 277 277V	PAINTED FINISHES BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK MG METALLIC GREY YL BRIGHT YELLOW BC BLACK CRINKLE G1 LIGHT GREY OR ORANGE	RG RIBBED GLASS ENCLOSURE PS³ PERFORATED METAL SLEEVE DIM⁴ DIMMING: 0-10V, ELV, OR TRIAC EMP⁵ EMERGENCY BATTERY PACK WH WHITE GLOSS T2 MEDIUM TAN AN METALLIC ANTHRACITE SF SEAFOAM MP MAGENTA PINK BZ METALLIC BRONZE SPECIAL COLOR FINISH SCF _____
NOTES 1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. CANNOT BE ORDERED WITH RIBBED GLASS ENCLOSURE (RG) 4. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC 5. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-1/4" DIAMETER CANOPY 6. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE				



Phone: 203.775.1805
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice