d5408
BELLA PENDANT

PROJECT:
TYPE:
QUANTITY:
NOTES:

SPECIFICATION

CONSTRUCTION	Precision-formed aluminum shade with clear glass enclosure and cast aluminum grill and fittings
CANOPY	5″ diameter black canopy
MOUNTING	Standard ceiling junction box
CORD	Black, Three-conductor hanging cord Adjustable-height aircraft cable
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED
DIMMING DRIVER	Optional dimming driver: 0-10V, ELV, or TRIAC
SHADE DIMENSION	24″ diameter x 15″ height
OVERALL HEIGHT	60″

DIMENSIONS



CANOPY OPTION

ORDERING INFORMATION

MODEL

☐ d5408

LAMPING

☐ LED16[2] 16W LED WITH ELECTRONIC DRIVER

VOLTAGE

☐ 120[1] 120V
☐ 277 277V

FINISH

PAINTED FINISHES

☐ BG BLACK GLOSS
☐ BL METALLIC BLUE
☐ RD METALLIC RED
☐ CU METALLIC COPPER
☐ T1 LIGHT TAN
☐ G2 MEDIUM GREY
☐ GM METALLIC GREEN
☐ MB MATTE BLACK
☐ MG METALLIC GREY
☐ YL BRIGHT YELLOW
☐ BC BLACK CRINKLE
☐ G1 LIGHT GREY
☐ OR ORANGE

☐ WH WHITE GLOSS
☐ T2 MEDIUM TAN
☐ AN METALLIC ANTHRACITE
☐ SF SEAFOAM
☐ MP MAGENTA PINK
☐ BZ METALLIC BRONZE

SPECIAL COLOR FINISH

☐ SCF _____

OPTIONS

☐ RG RIBBED GLASS ENCLOSURE
☐ PS[3] PERFORATED METAL SLEEVE[4]
☐ DIM[4] DIMMING: 0-10V, ELV, OR TRIAC
☐ EMP[5] EMERGENCY BATTERY PACK

NOTES

1. FIXTURES ARE FACTORY PREWIRED FOR 120V
2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K
3. CANNOT BE ORDERED WITH RIBBED GLASS ENCLOSURE (RG)
4. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC
5. REQUIRES A SEPARATE EM DRIVER THAT MAY AFFECT THE INSTALLATION AND PROFILE OF THE FIXTURE
6. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE

AL PA AN AB BG BL BZ CU G1 G2 GM MB MG MP RB RD SF T1 OR YL WH

Phone: 203.775.1805
P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
dacLighting.com | cs@dacLighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice