



# d5459

## MINI PELAGIC PENDANT


PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_

### SPECIFICATION

<b>CONSTRUCTION</b>	Spun-aluminum shade
<b>DIFFUSER</b>	Acrylic diffuser
<b>ACCENTS</b>	Polished chrome trim, clamps and loops
<b>CANOPY</b>	5" diameter black canopy
<b>MOUNTING</b>	Standard ceiling junction box
<b>STEM<sup>4</sup></b>	Black rigid 1/2" diameter stem
<b>FINISH</b>	Metal or powder-coat paint
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED
<b>DIMMING DRIVER</b>	Optional: 0-10V, ELV, or TRIAC
<b>SHADE DIMENSION</b>	9.5" diameter x 9" height
<b>OVERALL HEIGHT</b>	60"




### DIMENSIONS



### CANOPY OPTION



### ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5459 	<input type="checkbox"/> LED8 <sup>2</sup> 8W LED 700-800 LUMENS <input type="checkbox"/> LED15 <sup>2</sup> 15W LED, 1200-1400 LUMENS <input type="checkbox"/> 1M60 <sup>6</sup> 60W MAX, MEDIUM BASE, A TYPE	<input type="checkbox"/> 120 <sup>1</sup> 120V <input type="checkbox"/> 277 277V	<b>PAINTED FINISHES</b> <input type="checkbox"/> BG BLACK GLOSS <input type="checkbox"/> BL METALLIC BLUE <input type="checkbox"/> RD METALLIC RED <input type="checkbox"/> CU METALLIC COPPER <input type="checkbox"/> T1 LIGHT TAN <input type="checkbox"/> G2 MEDIUM GREY <input type="checkbox"/> GM METALLIC GREEN <input type="checkbox"/> MB MATTE BLACK <input type="checkbox"/> MG METALLIC GREY <input type="checkbox"/> YL BRIGHT YELLOW <input type="checkbox"/> PR PRUSSIAN BLUE <input type="checkbox"/> G1 LIGHT GREY <input type="checkbox"/> OR ORANGE	<input type="checkbox"/> DIM <sup>3</sup> DIMMING: 0-10V, ELV, OR TRIAC <input type="checkbox"/> EMP <sup>5</sup> EMERGENCY BATTERY PACK  <input type="checkbox"/> WH WHITE GLOSS <input type="checkbox"/> T2 MEDIUM TAN <input type="checkbox"/> AN METALLIC ANTHRACITE <input type="checkbox"/> SF SEAFOAM <input type="checkbox"/> MP MAGENTA PINK <input type="checkbox"/> BZ METALLIC BRONZE <b>SPECIAL COLOR FINISH</b> <input type="checkbox"/> SCF _____
<p align="center"><b>NOTES</b></p> <ol style="list-style-type: none"> <li>1. FIXTURES ARE FACTORY PREWIRED FOR 120V</li> <li>2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K</li> <li>3. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC</li> <li>4. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH</li> <li>5. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-1/4" DIAMETER CANOPY</li> <li>6. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC</li> <li>7. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE</li> </ol>				



Phone: 203.775.1805  
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

*As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice*