d5459
MINI PELAGIC PENDANT

PROJECT:
TYPE:
QUANTITY:
NOTES:

SPECIFICATION

CONSTRUCTION	Spun-aluminum shade
DIFFUSER	Acrylic diffuser
ACCENTS	Polished chrome trim, clamps and loops
CANOPY	5″ diameter black canopy
MOUNTING	Standard ceiling junction box
STEM[4]	Black rigid ½″ diameter stem
FINISH	Metal or powder-coat paint
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED
DIMMING DRIVER	Optional: 0-10V, ELV, or TRIAC
SHADE DIMENSION	9.5″ diameter x 9″ height
OVERALL HEIGHT	60″

DIMENSIONS



CANOPY OPTION

ORDERING INFORMATION

MODEL

- ☐ d5459

LAMPING

- ☐ LED8[2] 8W LED 700-800 LUMENS
- ☐ LED15[2] 15W LED, 1200-1400 LUMENS
- ☐ 1M60[6] 60W MAX, MEDIUM BASE, A TYPE

NOTES

1. FIXTURES ARE FACTORY PREWIRED FOR 120V
2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K
3. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC
4. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH
5. REQUIRES A SEPARATE EM DRIVER THAT MAY AFFECT THE INSTALLATION AND PROFILE OF THE FIXTURE
6. 120V ONLY. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC
7. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE

VOLTAGE

- ☐ 120[1] 120V
- ☐ 277 277V

FINISH

PAINTED FINISHES

- ☐ BG BLACK GLOSS
- ☐ BL METALLIC BLUE
- ☐ RD METALLIC RED
- ☐ CU METALLIC COPPER
- ☐ T1 LIGHT TAN
- ☐ G2 MEDIUM GREY
- ☐ GM METALLIC GREEN
- ☐ MB MATTE BLACK
- ☐ MG METALLIC GREY
- ☐ YL BRIGHT YELLOW
- ☐ PR PRUSSIAN BLUE
- ☐ G1 LIGHT GREY
- ☐ OR ORANGE

OPTIONS

- ☐ DIM[3] DIMMING: 0-10V, ELV, OR TRIAC
- ☐ EMP[5] EMERGENCY BATTERY PACK

- ☐ WH WHITE GLOSS
- ☐ T2 MEDIUM TAN
- ☐ AN METALLIC ANTHRACITE
- ☐ SF SEAFOAM
- ☐ MP MAGENTA PINK
- ☐ BZ METALLIC BRONZE

SPECIAL COLOR FINISH

- ☐ SCF _____

AL PA AN AB BG BL BZ CU G1 G2 GM MB MG MP RB RD SF T1 OR YL WH

Phone: 203.775.1805
P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
dacLighting.com | cs@dacLighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice