



d5460

SMALL PELAGIC PENDANT


PROJECT: _____
 TYPE: _____
 QUANTITY: _____
 NOTES: _____

SPECIFICATION

CONSTRUCTION	Spun-aluminum shade
DIFFUSER	Acrylic diffuser
ACCENTS	Polished chrome trim, clamps and loops
CANOPY	5" diameter black canopy
MOUNTING	Standard ceiling junction box
STEM⁴	Rigid 1/2" diameter stem
FINISH	Metal or powder-coat paint
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or medium base socket
DIMMING DRIVER	Optional: 0-10V, ELV, or TRIAC
OVERALL HEIGHT	60"
SHADE DIMENSION	13.75" diameter x 14.2" height



DIMENSIONS



CANOPY OPTION



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5460 	<input type="checkbox"/> 1M60 60W MAX, MEDIUM BASE, A TYPE <input type="checkbox"/> LED12 ² 12W LED, 1100 TOTAL LUMENS <input type="checkbox"/> LED25 ² 25W LED, 2500 TOTAL LUMENS <input type="checkbox"/> LED35 ² 35W LED, 3400 TOTAL LUMENS <input type="checkbox"/> LED40 ² 40W LED, 3800 TOTAL LUMENS	<input type="checkbox"/> 120 ¹ 120V <input type="checkbox"/> 277 277V	PAINTED FINISHES <input type="checkbox"/> BG BLACK GLOSS <input type="checkbox"/> BL METALLIC BLUE <input type="checkbox"/> RD METALLIC RED <input type="checkbox"/> CU METALLIC COPPER <input type="checkbox"/> T1 LIGHT TAN <input type="checkbox"/> G2 MEDIUM GREY <input type="checkbox"/> GM METALLIC GREEN <input type="checkbox"/> MB MATTE BLACK <input type="checkbox"/> MG METALLIC GREY <input type="checkbox"/> YL BRIGHT YELLOW <input type="checkbox"/> PR PRUSSIAN BLUE <input type="checkbox"/> G1 LIGHT GREY <input type="checkbox"/> OR ORANGE	<input type="checkbox"/> DIM ³ DIMMING: 0-10V, ELV, OR TRIAC <input type="checkbox"/> EMP ⁵ EMERGENCY BATTERY PACK <input type="checkbox"/> WH WHITE GLOSS <input type="checkbox"/> T2 MEDIUM TAN <input type="checkbox"/> AN METALLIC ANTHRACITE <input type="checkbox"/> SF SEAFOAM <input type="checkbox"/> MP MAGENTA PINK <input type="checkbox"/> BZ METALLIC BRONZE SPECIAL COLOR FINISH <input type="checkbox"/> SCF _____
NOTES 1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE 3. SPECIFY DIMMING PROTOCOL: 0-10V (FOR 35W/40W LED LAMPING, THE STEM OPTION MUST BE ADDED), ELV, OR TRIAC 4. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OAH 5. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-1/4" DIAMETER CANOPY 6. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE				



Phone: 203.775.1805
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice