



d5500 TEMPO PENDANT

PROJECT:
TYPE:
QUANTITY:
NOTES:

SPECIFICATION

CONSTRUCTION	20-gauge steel construction
DIFFUSER	Formed white opal acrylic with no open holes
MOUNTING	Standard ceiling junction box
STEM³	Rigid ½" diameter stem
FINISH	Metal or powder-coat paint
VOLTAGE	120V or 277V
LIGHT SOURCE	44W LED (24W uplight and 20W downlight)
LUMENS	4000lm
SHADE DIMENSION	33" diameter
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



DIMENSIONS

WITH OPTIONAL ROD



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
<input type="checkbox"/> d5500	LED44 ² 44W LED, 4000 LUMENS	120 ¹ 120V 277 277V	NI NICKEL PB POLISHED BRASS AB ANTIQUE BRASS WH POWDER COATED WHITE MB MATTE BLACK CH CHROME	ROD⁵ OPTIONAL DECORATIVE ROD EMP⁴ EMERGENCY BATTERY PACK
<p align="center">NOTES</p> <ol style="list-style-type: none"> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. FIXED LENGTH, NOT FIELD-ADJUSTABLE; CUSTOMER TO SPECIFY OVERALL HEIGHT 4. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-¼" DIAMETER CANOPY 5. CUSTOMER TO SPECIFY TYPE WHEN ORDERING 6. FOR ADDITIONAL MODIFICATIONS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE 				



AL PA AN AB BG BL BZ CU G1 G2 GM MB MG MP RB RD SF T1 OR YL WH



Phone: 203.775.1805
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice