



d8035

8-5/8" STRATO SQUARE CEILING/WALL FIXTURE

PROJECT: _____
 TYPE: _____
 QUANTITY: _____
 NOTES: _____

SPECIFICATION

CONSTRUCTION	Aluminum body
NUMBER OF TIERS	Four tiers
DIFFUSER	Sandblasted opal glass lens Perforated aluminum side diffuser
MOUNTING	Standard wall or ceiling junction box
FINISH	Brushed aluminum standard; consult factory for additional options
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or candelabra base socket
DIMENSIONS	8-5/8" width x 8-5/8" height
DEPTH	2-1/2"
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



DIMENSIONS



PRODUCT DETAIL



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
d8035	LED12² 12W LED, 1104 TOTAL LUMENS 2C40⁴ 40W MAX, CANDELABRA BASE, B-10 TYPE	120¹ 120V 277 277V	AL BRUSHED ALUMINUM PAINTED FINISHES BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK MG METALLIC GREY YL BRIGHT YELLOW BC BLACK CRINKLE G1 LIGHT GREY	DIM³ DIMMING: 0-10V, TRIAC, OR ELV WH WHITE GLOSS T2 MEDIUM TAN AN METALLIC ANTHRACITE SF SEAFOAM MP MAGENTA PINK BZ METALLIC BRONZE SPECIAL COLOR FINISH SCF _____
NOTES 1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED. 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V, ELV, OR TRIAC 4. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 5. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE				



Phone: 203.775.1805
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice