



# d8100

## BASIX CEILING/WALL FIXTURE

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_

### SPECIFICATION

|                        |   |
|------------------------|---|
| <b>CONSTRUCTION</b>    | Aluminum shade  |
| <b>DIFFUSER</b>        | White opal acrylic bottom lens                                |
| <b>MOUNTING</b>        | Standard ceiling or wall junction box                         |
| <b>FINISH</b>          | Metal or powder coat paint                                    |
| <b>VOLTAGE</b>         | 120V or 277V  |
| <b>LIGHT SOURCE</b>    | Dedicated LED or candelabra base socket                       |
| <b>DIMMING</b>         | Non-dimming, 0-10V, ELV, or TRIAC                             |
| <b>DIMENSIONS</b>      | 7-1/4" diameter   |
| <b>DEPTH</b>           | 3-7/8"  |
| <b>CODE COMPLIANCE</b> | UL listed, cUL (ETL/ETLc for LED) certified for dry locations |



### DIMENSIONS

### RELATED PRODUCT: d8101



### ORDERING INFORMATION

| MODEL   | LAMPING   | VOLTAGE  | FINISH  | OPTIONS  |
|---|---|--|---|--|
| d8100   | <b>LED6<sup>2</sup></b> 6W LED, 552 TOTAL LUMENS<br><b>2C25<sup>3</sup></b> 25W MAX, CANDELABRA BASE, B-10 TYPE | <b>120<sup>1</sup></b> 120V<br><b>277</b> 277V | <b>METAL FINISHES</b><br><b>AL</b> BRUSHED ALUMINUM<br><b>PA</b> POLISHED ALUMINUM<br><b>PAINTED FINISHES</b><br><b>BG</b> BLACK GLOSS<br><b>BL</b> METALLIC BLUE<br><b>RD</b> METALLIC RED<br><b>CU</b> METALLIC COPPER<br><b>T1</b> LIGHT TAN<br><b>G2</b> MEDIUM GREY<br><b>GM</b> METALLIC GREEN<br><b>MB</b> MATTE BLACK<br><b>MG</b> METALLIC GREY<br><b>YL</b> BRIGHT YELLOW | <b>DIM<sup>3</sup></b> DIMMING: 0-10V, TRIAC, OR ELV<br><b>EMP<sup>4</sup></b> EMERGENCY BATTERY PACK<br><b>WH</b> WHITE GLOSS<br><b>T2</b> MEDIUM TAN<br><b>AN</b> METALLIC ANTHRACITE<br><b>SF</b> SEAFOAM<br><b>MP</b> MAGENTA PINK<br><b>BZ</b> METALLIC BRONZE<br><b>SPECIAL COLOR FINISH</b><br><b>SCF</b> _____ |
| <b>NOTES</b><br>1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED.<br>2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K<br>3. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V, ELV, OR TRIAC<br>4. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-1/4" DIAMETER CANOPY<br>5. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC<br>6. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE |   |  |   |  |



Phone: 203.775.1805  
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

*As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice*