



d8103

BASIX CEILING/WALL FIXTURE


PROJECT: _____
 TYPE: _____
 QUANTITY: _____
 NOTES: _____

SPECIFICATION

| | |
|------------------------|---|
| CONSTRUCTION | Aluminum shade |
| DIFFUSER | White opal acrylic bottom lens |
| MOUNTING | Standard ceiling or wall junction box |
| FINISH | Metal or powder coat paint |
| VOLTAGE | 120V or 277V |
| LIGHT SOURCE | Dedicated LED or medium base socket |
| DIMMING | Non-dimming, 0-10V, ELV, or TRIAC |
| DIMENSIONS | 14-1/4" diameter |
| DEPTH | 8-5/8" |
| CODE COMPLIANCE | UL listed, cUL (ETL/ETLc for LED) certified for dry locations |



DIMENSIONS



RELATED PRODUCT:d8102



ORDERING INFORMATION

| MODEL | LAMPING | VOLTAGE | FINISH | OPTIONS |
|---|---|--|---|--|
| <input type="checkbox"/> d8102 | LED12² 12W LED, 1104 TOTAL LUMENS LED35² 35W LED, 3000-3300 LUMENS 1M100⁵ 100W MAX, MEDIUM BASE, A TYPE | 120¹ 120V 277 277V | METAL FINISHES AL BRUSHED ALUMINUM PA⁴ POLISHED ALUMINUM PAINTED FINISHES BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK MG METALLIC GREY YL BRIGHT YELLOW | DIM³ DIMMING: 0-10V, TRIAC, OR ELV EMP⁴ EMERGENCY BATTERY PACK WH WHITE GLOSS T2 MEDIUM TAN AN METALLIC ANTHRACITE SF SEAFOAM MP MAGENTA PINK BZ METALLIC BRONZE SPECIAL COLOR FINISH SCF _____ |
| NOTES 1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED. 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V, ELV, OR TRIAC 4. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-1/4" DIAMETER CANOPY 5. FIXTURE SUPPLIED LESS LAMPS; LAMPS MAY BE ORDERED FROM D'AC 6. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE | | | | |



Phone: 203.775.1805
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice