



d8111

MERIDIAN CEILING/WALL FIXTURE

PROJECT: _____
 TYPE: _____
 QUANTITY: _____
 NOTES: _____

SPECIFICATION

CONSTRUCTION	Aluminum shade
DIFFUSER	White opal acrylic bottom lens
ACCENTS	Brushed aluminum buttons
MOUNTING	Standard ceiling or wall junction box
FINISH	Metal or powder coat paint
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED or medium base socket
DIMMING	Non-dimming, 0-10V, ELV, or TRIAC
DIMENSIONS	9-1/4" diameter x 8-7/8" height
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



DIMENSIONS



RELATED PRODUCT: d8110



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	OPTIONS
d8111	LED8² 8W LED, 736 TOTAL LUMENS 1M75 75W MAX, MEDIUM BASE, A TYPE	120¹ 120V 277 277V	METAL FINISHES AL BRUSHED ALUMINUM PA POLISHED ALUMINUM PAINTED FINISHES BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK MG METALLIC GREY YL BRIGHT YELLOW	DIM³ DIMMING: 0-10V, TRIAC, OR ELV EMP⁴ EMERGENCY BATTERY PACK WH WHITE GLOSS T2 MEDIUM TAN AN METALLIC ANTHRACITE SF SEAFOAM MP MAGENTA PINK BZ METALLIC BRONZE SPECIAL COLOR FINISH SCF _____
NOTES 1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED. 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. COMPATIBLE WITH DEDICATED LED LAMPING; SPECIFY DIMMING PROTOCOL: 0-10V, ELV, OR TRIAC 4. THE EMERGENCY BATTERY PACK OPTION REQUIRES THE USE OF A 12-1/4" DIAMETER CANOPY 5. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE				



Phone: 203.775.1805
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice