



d8301

MOND CEILING/WALL FIXTURE

PROJECT: _____
 TYPE: _____
 QUANTITY: _____
 NOTES: _____



SPECIFICATION

CONSTRUCTION	Precision-formed aluminum
DIFFUSER	Acrylic diffuser
MOTION SENSOR	Microwave motion sensor automatically dims to 20% when space is unoccupied. Adjustable for time delay, light level, and occupancy sensor range
MOUNTING	Standard wall junction box
FINISH	Brushed metal finish standard
VOLTAGE	120V or 277V
LIGHT SOURCE	Dedicated LED
DIMENSIONS	14" diameter x 3.7" depth
CODE COMPLIANCE	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



DIMENSIONS

OPTIONAL EMERGENCY BATTERY PACK



ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	SHADE FINISH
d8301	LED18 ² 18W LED, 1611 TOTAL LUMENS	120 120V 277 277V	METAL FINISHES NI BRUSHED NICKEL PAINTED FINISHES BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK MG METALLIC GREY YL BRIGHT YELLOW BC BLACK CRINKLE	WH WHITE ACRYLIC WH WHITE GLOSS T2 MEDIUM TAN AN METALLIC ANTHRACITE SF SEAFOAM MP MAGENTA PINK BZ METALLIC BRONZE SPECIAL COLOR FINISH SCF _____
NOTES 1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED. 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE				



Phone: 203.775.1805
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice