



# d8302

## MOND CEILING/WALL FIXTURE

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_  
 NOTES: \_\_\_\_\_



### SPECIFICATION

<b>CONSTRUCTION</b>	Precision-formed aluminum
<b>DIFFUSER</b>	Acrylic diffuser
<b>MOTION SENSOR</b>	Microwave motion sensor automatically dims to 20% when space is unoccupied. Adjustable for time delay, light level, and occupancy sensor range
<b>MOUNTING</b>	Standard wall junction box
<b>FINISH</b>	Brushed metal finish standard
<b>VOLTAGE</b>	120V or 277V
<b>LIGHT SOURCE</b>	Dedicated LED
<b>DIMENSIONS</b>	17.75" diameter x 3.7" depth
<b>CODE COMPLIANCE</b>	UL listed, cUL (ETL/ETLc for LED) certified for dry locations



### DIMENSIONS

### OPTIONAL EMERGENCY BATTERY PACK



### ORDERING INFORMATION

MODEL	LAMPING	VOLTAGE	FINISH	SHADE FINISH
d8302	LED24 <sup>2</sup> 24W LED, 1815 TOTAL LUMENS	120 120V 277 277V	<b>METAL FINISHES</b> NI BRUSHED NICKEL <b>PAINTED FINISHES</b> BG BLACK GLOSS BL METALLIC BLUE RD METALLIC RED CU METALLIC COPPER T1 LIGHT TAN G2 MEDIUM GREY GM METALLIC GREEN MB MATTE BLACK MG METALLIC GREY YL BRIGHT YELLOW BC BLACK CRINKLE	WH WHITE ACRYLIC  WH WHITE GLOSS T2 MEDIUM TAN AN METALLIC ANTHRACITE SF SEAFOAM MP MAGENTA PINK BZ METALLIC BRONZE SPECIAL COLOR FINISH SCF _____
<b>NOTES</b> 1. FIXTURES ARE FACTORY PREWIRED FOR 120V UNLESS OTHERWISE SPECIFIED. 2. 3000K IS THE STANDARD COLOR TEMPERATURE UNLESS OTHERWISE SPECIFIED; ALSO AVAILABLE IN 2700K, 3500K, AND 4000K 3. FOR MODIFICATIONS TO DIMENSIONS, ELECTRICAL REQUIREMENTS, AND OTHER SPECIAL ORDERS, PLEASE CONTACT YOUR D'AC REPRESENTATIVE				



Phone: 203.775.1805  
 P.O. Box 165 | 20 Pocono Road | Brookfield CT 06804  
 daclighting.com | cs@daclighting.com

As part of d'ac's continuing efforts to improve the product line, fixtures may be modified or discontinued without prior notice